Contacts

> For a complete list of contact handle prefixes used across all TLDs, please refer to the **Contact Prefix Reference Table**

query-contact-list

Accepts:

pattern	pattern to match (against handle)
from	start from this item in list
to	end by this item in list
tld	limits output to contact handles which may be used with specified toplevel domain (tld), like "com".
extended-format	provides additional information for every contact listed: name & organization. May be "1" or "0", defaults to "0"

Returns:

List of registered contacts (handles), one per line.

When "extended-format" is requested, output columns are separated by tabs ("\t"), and "Columns" header provides column names.

Example:

```
https://dmapi.joker.com/request/query-contact-list?pattern=coco-47*&tld=com&auth-sid=<your-current-session-id>
```

contact-create

Requires:

tld	target TLD where this contact is intended to be used.
name	full name (if empty, fname + lname will be used)

fname	first name (required for .FI contacts)
lname	last name (required for .FI contacts)
title	(optional)
individual	(optional) Y, Yes, N, No
organization	(optional if individual)
email	email address of the contact
address-1	street address
address-2	(optional)
city	
state	(optional)
postal-code	
country	ISO country code (2 letters)
phone	
fax	(optional)
lang	language to use for .EU contacts
app-purpose	required for .US contacts
nexus-category	required for .US contacts
nexus-category-country	required for .US contacts
account-type	required for .UK contacts, if used as owner contact
company-number	required for .UK contacts with specific account types
orgid	required for .SE/.NU contacts
vatid	(optional) for .SE/.NU contacts
x-ficora-type	required for .FI contacts
x-ficora-is-finnish	(yes/no) required for .FI contacts
x-ficora-registernumber	required for .FI contacts, if ficora-type is company
x-ficora-identity	required for .FI contacts, if type is person and finnish
x-ficora-birthdate	required for .FI contacts, if type is persion and not finnish
x-ficora-legalemail	(optional) for .FI contacts

Either "name" or "lname" and "fname" must be provided.

Fields **not** marked '(optional)' are mandatory (and must not be empty).

Parameters "lname" and "fname", if provided, will be converted to "name" (simple concatenation of "fname" and "lname"), because registries support only "name" format. In general, use of "fname"

and "lname" is deprecated, and support for these fields will be removed in version 1.2.

"**orgid**" represents Swedish personal or organisational number and is required for .SE/.NU contacts.

It starts with ISO 3166 Alpha-2 country code in square brackets. If the country code for Sweden is given [SE] a valid Swedish personal or organisational number must be given (6 digits, dash, 4 digits), otherwise 1 to 123 characters can follow.

If organization is empty and the country code for Sweden [SE] is given, orgid must be a personal number, not an organisational number.

"**vatid**" is optional for .SE/.NU contacts. It starts with a two letter country code (uppercase), followed by an optional space, followed by a country specific string containing digits 0-9, and letters a-z and A-Z, maximum 64 Chars.

For .fi contacts:

"x-ficora-type" is required for .fi contacts. The following values are accepted: privateperson, company, corporation, institution, politicalparty, township, government, publiccommunity

"x-ficora-registernumber" is required if x-ficora-type is set to "company".

"x-ficora-is-finnish" is always required for .fi contacts: yes = finnish company or person, no = not a finnish person or company

"x-ficora-identity" is required for .fi contacts, if x-ficora-type is set to 'privateperson' and x-ficora-is-finnish is set to 'yes'

"x-ficora-birthdate" is required for .fi contacts, if x-ficora-type is set to 'privateperson' and x-ficora-is-finnish is set to 'no' in the following date format "YYYY-MM-DD".

For .uk contacts:

"account-type" is a required for all .UK contacts which will be used as domain owner contacts. Possible values are:

Value	Meaning
LTD	UK Limited Company
PLC	UK Public Limited Company
PTNR	UK Partnership
STRA	UK Sole Trader
LLP	UK Limited Liability Partnership

Value	Meaning
IP	UK Industrial/Provident Registered Company
IND	UK Individual (representing self)
SCH	UK School
RCHAR	UK Registered Charity
GOV	UK Government Body
CRC	UK Corporation by Royal Charter
STAT	UK Statutory Body
OTHER	UK Entity that does not fit into any of the above (e.g. clubs, associations, many universities)
FIND	Non-UK Individual (representing self)
FCORP	Non-UK Corporation
FOTHER	Non-UK Entity

By default, if **"account-type"** is not provided, value **"FIND"** or **"IND"** will be used (dependent **"country"** value - for GB and UK it will be **"IND"**, for everything else **"FIND"**).

"company-number" is required when "account-type" is one of: SCH, RCHAR, LTD, PLC, LLP, IP

Known extensions, grouped by TLD

.be

Extension	Value	Meaning
x-be-lang	(en|fr|nl)	Language for emails from the registry to contact.
x-be-type	(owner|admin|tech|licensee|onsite)	type for the contact
x-be-vatid		Vatid of the company

.ca

Extension	Value
x-ca-legal-type	(ABO|ASS|CCO|CCT|EDU|GOV|HOP|INB|LAM|LGR|MAJ|OMK|PLT|PRT|RES|TDM|TRD|TRS)

.cn

Extension	Value	Meaning

x-cn-owner-id-number	[\x20-\xff]{1,30}	Passport ID or company ID from official docs
x-cn-owner-id-type	(SFZ|HZ|GAJMTX|TWJMTX|WJLSFZ|GAJZZ|TWJZZ|JGZ|QT|ORG|QT|YYZZ|TYDM|BDDM|JDDWFW|SYDWFR|WGCZJG|SHTTFR|ZJCS|MBFQY|JJHFR|LSZY|WGZHWH|WLCZJG|SFJD|JWJG|SHFWJG|MBXXBX|YLJGZY|GZJGZY|BJWSXX|QTTYDM)	for I only (SFZ, HZ, GAJMTX, TWJMTX, WJLSFZ, GAJZZ, TWJZZ, JGZ, QT) allowed!
x-cn-owner-type	(E|I)	E=Enterprise, I=Individual

at, co.at, or.at

Extension	Value	Meaning
x-atnic-type	(privateperson|role|organisation)	type for the contact

.uk, .co.uk, .me.uk, .net.uk, .plc.uk, .org.uk, .ltd.uk

Extension	Value	Meaning
x-nominet-trading-name	[\x20-\xff]{1,50}	The trading name of the organization
x-nominet-company-no	[\x20-\xff]{1,30}	The registered company number
x-nominet-type	(LTD|PLC|PTNR|STRA|LLP|IP|IND|SCH|RCHAR|GOV|CRC|STAT|OTHER|FIND|FCORP|FOTHER)	account type

.de

Extension	Value	Meaning
x-de-type	(person|role|org)	type for the contact

.dk

Extension	Value	Meaning
x-dk-user-id-number	.*	user id for .dk domains
x-dk-user-type	(COMPANY|PERSON|PUBORG|ASSOCIATION)	user type for .dk domains

.eu, .xn--e1a4c, .xn--qxa6a

Extension	Value	Meaning
x-eu-natural-person	(true|false)	if set it is used
x-eu-country-of-citizenship	[A-Z]{2,2}	country code
x-eu-lang	(bg|cs|da|de|el|en|es|et|fi|fr|ga|hr|hu|it|lt|lv|mt|nl|pl|pt|ro|sk|sl|sv)	Sets the domain owners language displayed in the EURid WHOIS.
x-eu-type	(owner|admin|onsite)	type for the contact

.fi

Extension	Value	Meaning
x-ficora-birthdate	\d{4}-\d{2}-\d{2}	birthdate for owner contact
x-ficora-identity	([\w\-]{5,20})	identity number of private individuals
x-ficora-is-finnish	(yes|no)	Is it a Finnish person or company?
x-ficora-legalemail	!@email	if type=company, it must be present
x-ficora-registernumber	.{3,30}	registration number for companies
x-ficora-role	(billing|admin|tech|owner)	role of contact
x-ficora-type	(association|privateperson|company|corporation|institution|politicalparty|township|government|publiccommunity|municipality)	type of contact

.fr

Extension	Value	Meaning
x-fr-announce	\d+	"The ""announce"" attribute shows the number of the announcement(e.g. 5). Only digits allowed"
x-fr-birthcity	[\x20-\xff]{1,30}	Only for natural persons born in France...
x-fr-birthdate	\d{4}-\d{2}\-d{2}	The registrant's birthdate
x-fr-birthpc	[\x20-\xff]{1,30}	postcode of the place of birth
x-fr-birthplace	[A-Z]{2}	birthplace country code
x-fr-date-association	\d{4}-\d{2}\-d{2}	date of association
x-fr-date-publication-jo	\d{4}-\d{2}\-d{2}	date of publication JO
x-fr-duns	[\x20-\xff]{1,30}	Company DUNS

Extension	Value	Meaning
x-fr-local	[\x20-\xff]{1,30}	Company Local
x-fr-numero-de-page-announce-jo	\d+	page number of announcement
x-fr-restrict-pub	\d{1}	0=show, 1=do not show
x-fr-siren-or-siret	[\x20-\xff]{1,30}	SIREN/SIRET number
x-fr-trademark	[\x20-\xff]{1,30}	Trademark number
x-fr-vatid	[\x20-\xff]{1,30}	Company VAT ID
x-fr-waldec	\d+	Waldec ID

.ie

Extension	Value	Meaning
x-ie-applicant	.*	Name of applicant
x-ie-applicant-class	(Company|Business Owner|Club/Band/Local Group|School/College|State Agency|Blogger/Other)	

.it

Extension	Value
x-it-consentforpublishing	[0|1]
x-it-entity-type	[1|2|3|4|5|6|7]
x-it-regcode	(.*)
x-it-sect3-liability	[0|1]
x-it-sect5-personal-data-for-registration	[0|1]
x-it-sect6-personal-data-for-diffusion	[0|1]
x-it-sect7-explicit-acceptance	[0|1]

.nl

Extension	Value	Meaning

x-nl-legal-form	(ANDERS|BGG|BRO|BV|BVI/O|COOP|CV|EENMANSZAAK|EESV|KERK|MAATSCHAP|NV|OWM|PERSOON|REDR|STICHTING|VERENIGING|VOF)	legal form of the contact
x-nl-legal-form-registration-no	[\x20-\xff]{1,30}	registration number of the company.

.nu

Extension	Value	Meaning
x-iinu-orgid	[\x20-\xff]{1,30}	organisation id for the contact
x-iinu-vatid	[\x20-\xff]{1,30}	vatid for the contact

.se, .pp.se

Extension	Value	Meaning
x-iise-vatid	[\x20-\xff]{1,30}	vatid for the contact
x-iise-orgid	[\x20-\xff]{1,30}	organisation id for the contact

.sk

Extension	Value	Meaning
x-sk-contact-ident-number	.*	commercial registration number for companies; personal ID for natural persons
x-sk-contact-legal-form	(CORP|PERS)	CORP=Company/org; PERS=natural person

.us

Extension	Value	Meaning
x-us-app-purpose	[Pp][12345]	.us purpose of contact
x-us-nexus-category	([Cc])(11|12|21|31|32)	.us nexus category
x-us-nexus-category-country	!@country	.us nexus category country

.xxx

Extension	Value	Meaning
x-xxx-membership-token	[\x20-\xff]{1,30}	Registrar tag for domains

Please note:

- Parameters listed here (except "tld") may be used (or are required) in other requests, this is indicated by referring to "Contact fields".
- "lang" must contain two-letter ISO country (language) code, and is only required when creating .EU contacts. The purpose is to specify language to be used in notifications emails, sent from EURid. Please note - this field cannot be modified later, and the default is 'EN' (English)!
- "app-purpose", "nexus-category" and "nexus-category-contry" are required only when creating .US contacts, and cannot be modified later.

Example:

```
https://dmapi.joker.com/request/contact-create?tld=com&name=John Doe&email=johnd@someisp.com&address-1=Smartroad 1&city=Smalltown&postal-code=40122&country=US&phone=+1.422.8001&auth-sid=<your-current-session-id
```

contact-modify

Requires:

handle	contact handle to modify.

Accepts:

Field names exactly like in contact-create request, except that omitted fields won't be modified. That is, if you specify a field, it will be used as a new value, if you omit it, the old value will remain.

The field "tld" is not relevant for this request and will be ignored if present.

contact-delete

Requires:

handle	contact handle to delete

With this request you can delete previously registered contacts

Example:

```
https://dmapi.joker.com/request/contact-delete?handle=coco-4711&auth-sid=<your-current-session-id>
```

Revision #4
Created 2023-09-25 11:45:16 UTC by Admin
Updated 2023-10-05 09:00:31 UTC by Administrator