

# Domains

## Create an order

### Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
- xxx
- asia
- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registered with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name
- address-3

## ATTENTION

Please, refer to the table for the corresponding contact handles.

TLD	Contact handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>
me	COME-<number>
asia	COAS-<number>
xxx	CONX-<number>

## Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

tld	request field
-----	---------------

domains[0..500]	period	language[0..500]	
com	[a-z0-9-]{1,63}\.com	^([1..9]{1})\$	@language
net	[a-z0-9-]{1,63}\.net	^([1..9]{1})\$	
org	[a-z0-9-]{1,63}\.org	^([1..9]{1})\$	
info	[a-z0-9-]{1,63}\.info	^([1..9]{1})\$	
biz	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.biz	^([1..9]{1})\$	
mobi	[a-z0-9-]{1,63}\.mobi	^([1..9]{1})\$	
name	[a-z0-9-]{1,63}\.name	^[2..9]{1})\$	
us	[a-z0-9-]{1,63}\.us	^[2..9]{1})\$	
de	[a-z0-9-]{1,63}\.de	^([1..9]{1})\$	
cn	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.cn	^([1..9]{1})\$	
eu	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.eu	^([1..9]{1})\$	
me	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.me	^([1..9]{1})\$	
asia	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.asia	^([1..9]{1})\$	
xxx	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.xxx	^([1..9]{1})\$	
required	yes	yes	no (IDN domains only)

tld	owner-contact-handle	admin-contact-handle	tech-contact-handle	billing-contact-handle
-----	----------------------	----------------------	---------------------	------------------------

com	@comcont
net	@netcont
org	@orgcont
info	@infocont
biz	@decont
mobi	@mobicont
name	@namecont
us	@uscont
de	@bizcont
cn	@cncont
eu	@eucont
me	@mecont
asia	@asiacon
required	yes

tld	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle
<tld>	@ns					
required	yes	yes	no			

.COM order

**Example 1:** create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

domains0:xn--hans-mller-feb.com

language0:AFR

domains1:minus-10a.com

domains2:minus-10b.com

domains3:minus-10c.com

domains4:minus-10d.com  
domains5:minus-10e.com  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

domains0:minus-109.com  
domains1:minus-10a.com  
domains2:minus-10b.com  
domains3:minus-10c.com  
domains4:minus-10d.com  
domains5:minus-10e.com  
period:2  
owner-contact-handle:CCOM-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create com-order with implicit contact-handle-creation of all contacts

subject: create com-order [your reference id]

domains0:minus-109.com  
domains1:minus-10a.com  
domains2:minus-10b.com  
domains3:minus-10c.com  
domains4:minus-10d.com  
domains5:minus-10e.com  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1

ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

.NET order

**Example 1:** create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

domains0:xn--hans-mller-feb.net  
language0:AFR  
domains1:minus-10a.net  
domains2:minus-10b.net  
domains3:minus-10c.net  
domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

domains0:minus-109.net  
domains1:minus-10a.net

domains2:minus-10b.net  
domains3:minus-10c.net  
domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-handle:CCOM-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CCOM-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

domains0:minus-109.net  
domains1:minus-10a.net  
domains2:minus-10b.net  
domains3:minus-10c.net  
domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net



tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

.ORG order

**Example 1:** create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]

domains0:xn--hans-mller-feb.org  
language0:AFR  
domains1:minus-10a.org  
domains2:minus-10b.org  
domains3:minus-10c.org  
domains4:minus-10d.org  
domains5:minus-10e.org  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo

owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CORG-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create org-order with implicit nameserver-creation

subject: create org-order [your reference id]

domains0:minus-109.org  
domains1:minus-10a.org  
domains2:minus-10b.org  
domains3:minus-10c.org  
domains4:minus-10d.org  
domains5:minus-10e.org  
period:2  
owner-contact-handle:CORG-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CORG-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create org-order with implicit contact-handle-creation of all contacts

subject: create org-order [your reference id]

domains0:minus-109.org  
domains1:minus-10a.org  
domains2:minus-10b.org  
domains3:minus-10c.org  
domains4:minus-10d.org  
domains5:minus-10e.org  
period:2

owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

.INFO order

**Example 1:** create info-order with implicit contact-handle-creation of the owner-contact

subject: create info-order [your reference id]

domains0:xn--hans-mller-feb.info  
language0:AFR  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:C282828-LRMS  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

domains0:minus-109.info  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2  
owner-contact-handle:C176269-LRMS  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:C176219-LRMS

ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

domains0:minus-109.info  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net

billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

.BIZ order

**Example 1:** create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz  
language0:AFR  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711

admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 2:** create biz-order with implicit nameserver-creation

subject: create biz-order [your reference id]

domains0:minus-109.biz  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-handle:CNEU-123  
admin-contact-handle:CNEU-124  
tech-contact-handle:CNEU-125  
billing-contact-handle:CNEU-126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create biz-order with implicit contact-handle-creation of all contacts

subject: create biz-order [your reference id]

domains0:minus-109.biz  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase



billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .MOBI ORDER

**Example 1:** create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

domains0:xn--hans-mller-feb.mobi  
language0:AFR  
domains1:minus-10a.mobi  
domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COMO-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

domains0:minus-109.mobi  
domains1:minus-10a.mobi  
domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-handle:COMO-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COMO-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

domains0:minus-109.mobi  
domains1:minus-10a.mobi  
domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews

admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

.NAME ORDER

**Example 1:** create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]

domains0:xn--hans-mller-feb.net  
language0:AFR  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name

domains5:minus-10e.name  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CNAM-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create name-order with implicit nameserver-creation

subject: create name-order [your reference id]

domains0:minus-109.name  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-handle:CNAM-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CNAM-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create name-order with implicit contact-handle-creation of all contacts

subject: create name-order [your reference id]

domains0:minus-109.name  
domains1:minus-10a.name

domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

.US ORDER

**Example 1:** create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mller-feb.us  
language0:AFR  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us

period:2  
owner-contact-handle:COUS-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews

tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## ■ DE ORDER

**Example 1:** create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de  
language0:GER  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nase  
owner-contact-address-1:Musterstrasse 11  
owner-contact-postal-code:4711  
owner-contact-city:Musterhausen  
owner-contact-country:DE  
owner-contact-phone:49 13383794 504040  
owner-contact-fax:49 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CODE-1007  
ns1-handle:ns.gonzo.net



ns2-handle:ns2.gonzo.net

**Example 2:** create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

domains0:minus-109.de  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-handle:CODE-1007  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CODE-1007  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nase  
owner-contact-address-1:Musterstrasse 11  
owner-contact-postal-code:4711  
owner-contact-city:Musterhausen  
owner-contact-country:DE  
owner-contact-phone:49 13383794 504040  
owner-contact-fax:49 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nase  
admin-contact-address-1:Musterstrasse 11  
admin-contact-postal-code:4711  
admin-contact-city:Musterhausen  
admin-contact-country:DE  
admin-contact-phone:49 13383794 504040  
admin-contact-fax:49 13383794 504040  
tech-contact-email:gonzo@nose.net

tech-contact-individual:Y  
tech-contact-fname:gonzo  
tech-contact-lname:nase  
tech-contact-address-1:Musterstrasse 11  
tech-contact-postal-code:4711  
tech-contact-city:Musterhausen  
tech-contact-country:DE  
tech-contact-phone:49 13383794 504040  
tech-contact-fax:49 13383794 504040  
billing-contact-email:gonzo@nose.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nase  
billing-contact-address-1:Musterstrasse 11  
billing-contact-postal-code:4711  
billing-contact-city:Musterhausen  
billing-contact-country:DE  
billing-contact-phone:49 13383794 504040  
billing-contact-fax:49 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .CN ORDER

**Example 1:** create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711

admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 2:** create cn-order using existing cn-handles

subject: create cn-order [your reference id]

domains0:minus-109.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-handle:COCN-123  
admin-contact-handle:COCN-124  
tech-contact-handle:COCN-125  
billing-contact-handle:COCN-126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create cn-order with backreferences using @same-as

subject: create cn-order [your reference id]

domains0:minus-109.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn

period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .EU ORDER

**Example 1:** create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi

tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 2:** create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-handle:C123123  
admin-contact-handle:C123124  
tech-contact-handle:C123125  
billing-contact-handle:C123126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose

owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

# Modify a domain

## Introduction

renew <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s),
- the renewalperiod or the desired expiryyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to

check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

## Request fields

mailsubject: renew <tld>-domain [your reference id]

Definition of this request

You have to provide the domain name and the renewal period or the desired expire year using the format "YYYY" on one line. You have to separate each field with a ":" (ASCII 058). The maximum for the renewal period is 9 years.

request-field	valid values	required
domains[0..500]	[a-z0-9-]{1,63}\.<tld>:([1-9])\d{4}	yes

.COM renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:4

domains1:minus-119.com:4

domains2:minus-129.com:4

domains3:minus-139.com:4

domains4:minus-149.com:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

domains1:minus-119.com:2  
domains2:minus-129.com:3  
domains3:minus-139.com:4  
domains4:minus-149.com:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew com-domain [your reference id]

domains0:minus-109.com:2005

.NET Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:4  
domains1:minus-119.net:4  
domains2:minus-129.net:4  
domains3:minus-139.net:4  
domains4:minus-149.net:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1  
domains1:minus-119.net:2  
domains2:minus-129.net:3  
domains3:minus-139.net:4  
domains4:minus-149.net:5



**Example 4:** renew 1 domain using the field expirationyear

subject: renew net-domain [your reference id]

domains0:minus-109.net:2005

.ORG Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:4

domains1:minus-119.org:4

domains2:minus-129.org:4

domains3:minus-139.org:4

domains4:minus-149.org:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

domains1:minus-119.org:2

domains2:minus-129.org:3

domains3:minus-139.org:4

domains4:minus-149.org:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew org-domain [your reference id]

domains0:minus-109.org:2005

## .INFO Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:4

domains1:minus-119.info:4

domains2:minus-129.info:4

domains3:minus-139.info:4

domains4:minus-149.info:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

domains1:minus-119.info:2

domains2:minus-129.info:3

domains3:minus-139.info:4

domains4:minus-149.info:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew info-domain [your reference id]

domains0:minus-109.info:2005

## .BIZ Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:4

domains1:minus-119.biz:4

domains2:minus-129.biz:4

domains3:minus-139.biz:4

domains4:minus-149.biz:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1

domains1:minus-119.biz:2

domains2:minus-129.biz:3

domains3:minus-139.biz:4

domains4:minus-149.biz:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:2005

.NAME Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:4  
domains1:minus-119.name:4  
domains2:minus-129.name:4  
domains3:minus-139.name:4  
domains4:minus-149.name:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1  
domains1:minus-119.name:2  
domains2:minus-129.name:3  
domains3:minus-139.name:4  
domains4:minus-149.name:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew name-domain [your reference id]

domains0:minus-109.name:2005

.US Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:4  
domains1:minus-119.us:4  
domains2:minus-129.us:4  
domains3:minus-139.us:4  
domains4:minus-149.us:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

domains1:minus-119.us:2

domains2:minus-129.us:3

domains3:minus-139.us:4

domains4:minus-149.us:5

**Example 4:** renew 1 domain using the field expire year

subject: renew us-domain [your reference id]

domains0:minus-109.net:2005

.DE Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:4

domains1:minus-119.de:4

domains2:minus-129.de:4

domains3:minus-139.de:4

domains4:minus-149.de:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1  
domains1:minus-119.de:2  
domains2:minus-129.de:3  
domains3:minus-139.de:4  
domains4:minus-149.de:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew de-domain [your reference id]

domains0:minus-109.de:2005

.CN Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:4  
domains1:minus-119.cn:4  
domains2:minus-129.cn:4  
domains3:minus-139.cn:4  
domains4:minus-149.cn:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1  
domains1:minus-119.cn:2  
domains2:minus-129.cn:3  
domains3:minus-139.cn:4  
domains4:minus-149.cn:5

**Example 4:** renew 1 domain using the field expire year

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:2005

# Renew a domain

## Introduction

renew <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s),
- the renewalperiod or the desired expiryyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

## Request fields

mailsubject: renew <tld>-domain [your reference id]

### Definition of this request

You have to provide the domain name and the renewal period or the desired expire year using the format "YYYY" on one line. You have to separate each field with a ":" (ASCII 058). The maximum for the renewal period is 9 years.

request-field	valid values	required
domains[0..500]	[a-z0-9-]{1,63}\.<tld>:([1-9])\d{4}	yes

### .COM renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:4

domains1:minus-119.com:4

domains2:minus-129.com:4

domains3:minus-139.com:4

domains4:minus-149.com:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

domains1:minus-119.com:2

domains2:minus-129.com:3

domains3:minus-139.com:4

domains4:minus-149.com:5



**Example 4:** renew 1 domain using the field expirationyear

subject: renew com-domain [your reference id]

domains0:minus-109.com:2005

.NET Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:4

domains1:minus-119.net:4

domains2:minus-129.net:4

domains3:minus-139.net:4

domains4:minus-149.net:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1

domains1:minus-119.net:2

domains2:minus-129.net:3

domains3:minus-139.net:4

domains4:minus-149.net:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew net-domain [your reference id]

domains0:minus-109.net:2005

.ORG Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:4

domains1:minus-119.org:4

domains2:minus-129.org:4

domains3:minus-139.org:4

domains4:minus-149.org:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

domains1:minus-119.org:2

domains2:minus-129.org:3

domains3:minus-139.org:4

domains4:minus-149.org:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew org-domain [your reference id]

domains0:minus-109.org:2005

## .INFO Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:4

domains1:minus-119.info:4

domains2:minus-129.info:4

domains3:minus-139.info:4

domains4:minus-149.info:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

domains1:minus-119.info:2

domains2:minus-129.info:3

domains3:minus-139.info:4

domains4:minus-149.info:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew info-domain [your reference id]

domains0:minus-109.info:2005

## .BIZ Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:4  
domains1:minus-119.biz:4  
domains2:minus-129.biz:4  
domains3:minus-139.biz:4  
domains4:minus-149.biz:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1  
domains1:minus-119.biz:2  
domains2:minus-129.biz:3  
domains3:minus-139.biz:4  
domains4:minus-149.biz:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:2005

.NAME Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:4

domains1:minus-119.name:4  
domains2:minus-129.name:4  
domains3:minus-139.name:4  
domains4:minus-149.name:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1  
domains1:minus-119.name:2  
domains2:minus-129.name:3  
domains3:minus-139.name:4  
domains4:minus-149.name:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew name-domain [your reference id]

domains0:minus-109.name:2005

.US Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:4  
domains1:minus-119.us:4  
domains2:minus-129.us:4  
domains3:minus-139.us:4  
domains4:minus-149.us:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

domains1:minus-119.us:2

domains2:minus-129.us:3

domains3:minus-139.us:4

domains4:minus-149.us:5

**Example 4:** renew 1 domain using the field expire year

subject: renew us-domain [your reference id]

domains0:minus-109.net:2005

.DE Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:4

domains1:minus-119.de:4

domains2:minus-129.de:4

domains3:minus-139.de:4

domains4:minus-149.de:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1

domains1:minus-119.de:2  
domains2:minus-129.de:3  
domains3:minus-139.de:4  
domains4:minus-149.de:5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew de-domain [your reference id]

domains0:minus-109.de:2005

.CN Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:4  
domains1:minus-119.cn:4  
domains2:minus-129.cn:4  
domains3:minus-139.cn:4  
domains4:minus-149.cn:4

**Example 3:** renew 5 domains for different years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1  
domains1:minus-119.cn:2  
domains2:minus-129.cn:3  
domains3:minus-139.cn:4  
domains4:minus-149.cn:5

**Example 4:** renew 1 domain using the field expire year

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:2005

# Transfer a domain

## Introduction

transfer <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can transfer a domain from 1 registrar to Joker.com.

You have to provide the following information within the request:

- the domain name,
- the auth-id,
- the billing-contact-handle,

You can transfer 1 com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we don't need information about the owner-contact. We will detect this information from the whois of the current registrar and we will create the contact-handle for the owner-contact automatically.



You need to provide us with a so called auth-id. You have to ask the current registrar for this auth-id. If you provide an invalid auth-id, the transfer will be declined by the current registrar.

As you can see, we need the billing-contact-handle. **We recommend using a billing-handle with the email-address of your "robot-email". If you use a contact-handle with a different e-mail than your robot e-mail, you can't administer the transferred domain using the webinterface and the person with access to the email, which is shown in the provided billing-handle will have access using the web-interface.**

If you don't have a com-contact-handle with your "robot-email", you have to create a com-handle using the "create com-contact" request.

We do not need information about the nameservers. This information will be detected from the whois of the current registrar and we will create the nameservers if necessary.

This procedure implies, that an owner change or change of nameservers during the transfer-process is not possible.

## Request fields

mailsubject: transfer <tld>-domain [your reference id]

### ATTENTION:

You can transfer 1 domain with one request.

Definition of this request

request-field	valid values	required
domains0	[a-z0-9-]{1,63}\.<tld>	yes
auth-id	.*	yes
billing-contact-handle	Please, refer to the table below.	yes

tld	billing-contact-handle
com	@comcont
net	@netcont
org	@orgcont
info	@infocont
biz	@bizcont
mobi	@mobicont

name	@namecont
us	@uscont
de	@decont
cn	@cncont
eu	@eucont

TRANSFER COM DOMAIN

**Example 1:** transfer com-domain

subject: transfer com-domain [your reference id]  
domains0:minus-109.com  
auth-id:0293XaAdA  
billing-contact-handle:CCOM-1234

TRANSFER NET DOMAIN

**Example 1:** transfer net-domain

subject: transfer net-domain [your reference id]  
  
domains0:minus-109.net  
auth-id:0293XaAdA  
billing-contact-handle:CNET-1234

TRANSFER ORG DOMAIN

**Example 1:** transfer org-domain

subject: transfer org-domain [your reference id]  
  
domains0:minus-109.org  
auth-id:0293XaAdA  
billing-contact-handle:CORG-1234

TRANSFER INFO DOMAIN

**Example 1:** transfer info-domain

subject: transfer info-domain [your reference id]  
  
domains0:minus-109.info

auth-id:0293XaAdA  
billing-contact-handle:C176269-LRMS

## TRANSFER BIZ DOMAIN

### **Example 1:** transfer biz-domain

subject: transfer biz-domain [your reference id]

domains0:minus-109.biz  
auth-id:0293XaAdA  
billing-contact-handle:CNEU-123

## TRANSFER NAME DOMAIN

### **Example 1:** transfer name-domain

subject: transfer name-domain [your reference id]

domains0:minus-109.name  
auth-id:0293XaAdA  
billing-contact-handle:CNAM-1234

## TRANSFER US DOMAIN

### **Example 1:** transfer us-domain

subject: transfer us-domain [your reference id]

domains0:minus-109.us  
auth-id:0293XaAdA  
billing-contact-handle:COUS-1234

## TRANSFER DE DOMAIN

### **Example 1:** transfer de-domain

subject: transfer de-domain [your reference id]

domains0:minus-109.de  
auth-id:0293XaAdA  
billing-contact-handle:CODE-1234

## TRANSFER CN DOMAIN

### **Example 1:** transfer cn-domain

subject: transfer cn-domain [your reference id]

domains0:minus-109.cn

auth-id:0293XaAdA

billing-contact-handle:COCN-1234

# Delete a domain

## **Introduction**

With this request you can delete a domain at Joker.com.

You have to provide the following information within the request:

- domain name(s),
- the special flag force

### **ATTENTION:**

If you delete a domain within the first 72 hours after the registration, the registration-fee will be refunded to your account.

If Joker.com receives the delete-request more than 72 hours after the registration, you have to provide the flag "force:1", in order to accept that the registration-fee will not be refunded to your account. If you do not send the "force:1" in such a case, the request will be rejected.

## **Request fields**

mailsubject: delete domain [your reference id]

Definition of this request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

request-field	valid values	required
tld	(com net org info biz mobi name de cn eu us)	yes
sld	[a-z0-9-]{1,63}	yes
force	1 0	no

## DELETE COM DOMAIN

**Example 1:** delete a domain during the first 72 hours after registration

subject: delete domain [your reference id]

tld:com  
sld:frezel

**Example 2:** delete a domain after the first 72 hours after registration

subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:1

**Example 3:** delete a domain only for the case that a refund is possible!

subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:0

# List domains

## Introduction

list domains

With this request you can get a list (lexicographically sorted) of all the domains, you have currently registered at joker.com.

You have to provide the target-registry within the request:

```
cno = .com/.net
com = .net
net = .net
org = .org
info = .info
biz = .biz
mobi = .mobi
name = .mobi
de = .de
cn = .cn
eu = .eu
us = .us
```

### LIMITATIONS:

- Only 20.000 domains are listed. If you have more than 20.000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20.000 domains at joker.com under 1 registry, this request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

### Request fields

mailsubject: list domains [your reference id]

Definition of this request:

request-field	valid values	required
target	com net org info mobi name biz de cn eu us	yes

### LIST DOMAINS

**Example 1:** list domains for .com-domains

subject: list domains [your reference id]

target:com

**Example 2:** list domains for .net-domains

subject: list domains [your reference id]

target:net

**Example 3:** list domains for .org-domains

subject: list domains [your reference id]

target:org

**Example 4:** list domains for .info-domains

subject: list domains [your reference id]

target:info

**Example 5:** list domains for .biz-domains

subject: list domains [your reference id]

target:biz

**Example 6:** list domains for .de-domains

subject: list domains [your reference id]

target:de

**Example 7:** list domains for .cn-domains

subject: list domains [your reference id]

target:cn

# Lock a domain

## Introduction

lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer-request from a foreign registrar will be declined.

You have to provide the following information within the request:

- domain name

You can lock 1 domain with one request.

## Request fields

mailsubject: lock domain [your reference id]

Definition of this request

request-field	valid values	required
fqdn	@fqdn	yes

## Example 1: lock a domain

subject: lock domain [your reference id]

fqdn:minus-109.com

# Unlock a domain

## Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following informations within the request:

- domain name

You can unlock 1 domain with one request.



## Request fields

mailsubject: unlock domain [your reference id]

Definitions of this request

request-field	valid values	required
fqdn	@fqdn	yes

## Example 1: unlock a domain

subject: unlock domain [your reference id]

fqdn:minus-109.com

# Get Auth-id

## Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLD's .org/.info/.biz.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

## Request fields

mailsubject: get auth-id [your reference id]

Definition of this request

request-field	valid values						required
fqdn	@orgdom	@infodom	@bizdom	@cndom	@eudom	@usdom	yes

**Example 1:** retrieve the auth-id for a .org-domain

subject: get auth-id [your reference id]

fqdn:minus-109.org

**Example 2:** retrieve the auth-id for a .biz-domain

subject: get auth-id [your reference id]

fqdn:minus-109.biz

**Example 3:** retrieve the auth-id for a .eu-domain

subject: get auth-id [your reference id]

fqdn:minus-109.eu

# Grant Roles/Domain Permissions, Internal Transfer

## Introduction

With this request you can assign 'Roles' (permissions) of domains to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user. In this case, the domain is assigned to the receiving account, including all rights and permissions on this domain.

There are two variants to use this functionality: If the user id (Joker.com user account id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (=> Transfer). This can also be used for users which do not yet have a Joker.com account.

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "reseller id" - must match the 'destination client email')
- desired role (type of permission you want to assign to "client email" resp. "client id" - one of "admin|tech|billing|creator"; "creator" means "all permissions" and is equivalent to an **internal transfer** or 'assignment' - also see 'roles ')

## Request fields

mailsubject: joker-internal-transfer [your reference id]

Definition of this request

Valid values for <tld>: **all** Joker.com tlds

request-field	valid values	required
fqdn	[a-z0-9-]{1,63}\.<tld>	yes
destination-client-email	@email	yes
destination-client-id	[0-9]+	no
desired-role	admin tech billing creator (if omitted, default is 'creator')	no

**Example 1:** assign 'billing'-role to user 123456 (direct)

subject: joker-internal-transfer [your reference id]

body:  
fqdn:exampledomain.com  
destination-client-email:example-user@gmail.com  
destination-client-id:123456  
desired-role:billing

**Example 2:** assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: joker-internal-transfer [your reference id]

body:

fqdn:exampledomain.com

destination-client-email:example-user@gmail.com

desired-role:creator

---

Revision #1

Created 25 September 2023 11:51:19 by Admin

Updated 5 October 2023 09:00:31 by Admin