

Domains

Create an order

Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
- xxx
- asia
- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registered with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name
- address-3

ATTENTION

Please, refer to the table for the corresponding contact handles.

TLD	Contact handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>
me	COME-<number>
asia	COAS-<number>
xxx	CONX-<number>

Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

tld	request field
-----	---------------

domains[0..500]	period	language[0..500]	
com	[a-z0-9-]{1,63}\.com	^([1..9]{1})\$	@language
net	[a-z0-9-]{1,63}\.net	^([1..9]{1})\$	
org	[a-z0-9-]{1,63}\.org	^([1..9]{1})\$	
info	[a-z0-9-]{1,63}\.info	^([1..9]{1})\$	
biz	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.biz	^([1..9]{1})\$	
mobi	[a-z0-9-]{1,63}\.mobi	^([1..9]{1})\$	
name	[a-z0-9-]{1,63}\.name	^[2..9]{1})\$	
us	[a-z0-9-]{1,63}\.us	^[2..9]{1})\$	
de	[a-z0-9-]{1,63}\.de	^([1..9]{1})\$	
cn	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.cn	^([1..9]{1})\$	
eu	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.eu	^([1..9]{1})\$	
me	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.me	^([1..9]{1})\$	
asia	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.asia	^([1..9]{1})\$	
xxx	[a-z0-9][a-z0-9-]{1,61}[a-z0-9]\.xxx	^([1..9]{1})\$	
required	yes	yes	no (IDN domains only)

tld	owner-contact-handle	admin-contact-handle	tech-contact-handle	billing-contact-handle
-----	----------------------	----------------------	---------------------	------------------------

com	@comcont
net	@netcont
org	@orgcont
info	@infocont
biz	@decont
mobi	@mobicont
name	@namecont
us	@uscont
de	@bizcont
cn	@cncont
eu	@eucont
me	@mecont
asia	@asiacon
required	yes

tld	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle
<tld>	@ns					
required	yes	yes	no			

.COM order

Example 1: create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

domains0:xn--hans-mller-feb.com

language0:AFR

domains1:minus-10a.com

domains2:minus-10b.com

domains3:minus-10c.com

domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create com-order with implicit contact-handle-creation of all contacts

subject: create com-order [your reference id]

domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1

ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NET order

Example 1: create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

domains0:minus-109.net
domains1:minus-10a.net

domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net

tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.ORG order

Example 1: create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]

domains0:xn--hans-mller-feb.org
language0:AFR
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo

owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create org-order with implicit nameserver-creation

subject: create org-order [your reference id]

domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-handle:CORG-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create org-order with implicit contact-handle-creation of all contacts

subject: create org-order [your reference id]

domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2

owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.INFO order

Example 1: create info-order with implicit contact-handle-creation of the owner-contact

subject: create info-order [your reference id]

domains0:xn--hans-mller-feb.info
language0:AFR
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C282828-LRMS
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-handle:C176269-LRMS
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:C176219-LRMS

ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

domains0:minus-109.info
domains1:minus-10a.info
domains2:minus-10b.info
domains3:minus-10c.info
domains4:minus-10d.info
domains5:minus-10e.info
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net

billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.BIZ order

Example 1: create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz
language0:AFR
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711

admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create biz-order with implicit nameserver-creation

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-handle:CNEU-123
admin-contact-handle:CNEU-124
tech-contact-handle:CNEU-125
billing-contact-handle:CNEU-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create biz-order with implicit contact-handle-creation of all contacts

subject: create biz-order [your reference id]

domains0:minus-109.biz
domains1:minus-10a.biz
domains2:minus-10b.biz
domains3:minus-10c.biz
domains4:minus-10d.biz
domains5:minus-10e.biz
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase

billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.MOBI ORDER

Example 1: create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

domains0:xn--hans-mller-feb.mobi
language0:AFR
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-handle:COMO-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COMO-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

domains0:minus-109.mobi
domains1:minus-10a.mobi
domains2:minus-10b.mobi
domains3:minus-10c.mobi
domains4:minus-10d.mobi
domains5:minus-10e.mobi
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews

admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.NAME ORDER

Example 1: create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]

domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name

domains5:minus-10e.name
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create name-order with implicit nameserver-creation

subject: create name-order [your reference id]

domains0:minus-109.name
domains1:minus-10a.name
domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-handle:CNAM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CNAM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create name-order with implicit contact-handle-creation of all contacts

subject: create name-order [your reference id]

domains0:minus-109.name
domains1:minus-10a.name

domains2:minus-10b.name
domains3:minus-10c.name
domains4:minus-10d.name
domains5:minus-10e.name
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.US ORDER

Example 1: create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mller-feb.us
language0:AFR
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net

Example 2: create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us

period:2
owner-contact-handle:COUS-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:COUS-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us
domains1:minus-10a.us
domains2:minus-10b.us
domains3:minus-10c.us
domains4:minus-10d.us
domains5:minus-10e.us
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews

tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

■ DE ORDER

Example 1: create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de
language0:GER
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nase
owner-contact-address-1:Musterstrasse 11
owner-contact-postal-code:4711
owner-contact-city:Musterhausen
owner-contact-country:DE
owner-contact-phone:49 13383794 504040
owner-contact-fax:49 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CODE-1007
ns1-handle:ns.gonzo.net

ns2-handle:ns2.gonzo.net

Example 2: create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

domains0:minus-109.de
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-handle:CODE-1007
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CODE-1007
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de
domains1:minus-10a.de
domains2:minus-10b.de
domains3:minus-10c.de
domains4:minus-10d.de
domains5:minus-10e.de
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nase
owner-contact-address-1:Musterstrasse 11
owner-contact-postal-code:4711
owner-contact-city:Musterhausen
owner-contact-country:DE
owner-contact-phone:49 13383794 504040
owner-contact-fax:49 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nase
admin-contact-address-1:Musterstrasse 11
admin-contact-postal-code:4711
admin-contact-city:Musterhausen
admin-contact-country:DE
admin-contact-phone:49 13383794 504040
admin-contact-fax:49 13383794 504040
tech-contact-email:gonzo@nose.net

tech-contact-individual:Y
tech-contact-fname:gonzo
tech-contact-lname:nase
tech-contact-address-1:Musterstrasse 11
tech-contact-postal-code:4711
tech-contact-city:Musterhausen
tech-contact-country:DE
tech-contact-phone:49 13383794 504040
tech-contact-fax:49 13383794 504040
billing-contact-email:gonzo@nose.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nase
billing-contact-address-1:Musterstrasse 11
billing-contact-postal-code:4711
billing-contact-city:Musterhausen
billing-contact-country:DE
billing-contact-phone:49 13383794 504040
billing-contact-fax:49 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.CN ORDER

Example 1: create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711

admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi
tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create cn-order using existing cn-handles

subject: create cn-order [your reference id]

domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn
period:2
owner-contact-handle:COCN-123
admin-contact-handle:COCN-124
tech-contact-handle:COCN-125
billing-contact-handle:COCN-126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create cn-order with backreferences using @same-as

subject: create cn-order [your reference id]

domains0:minus-109.cn
domains1:minus-10a.cn
domains2:minus-10b.cn
domains3:minus-10c.cn
domains4:minus-10d.cn
domains5:minus-10e.cn

period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

.EU ORDER

Example 1: create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-email:gonzo@nose.net
admin-contact-individual:Y
admin-contact-fname:gonzo
admin-contact-lname:nose
admin-contact-address-1:horsefair mews
admin-contact-city:romsey
admin-contact-postal-code:4711
admin-contact-country:DE
admin-contact-phone:44 13383794 504040
tech-contact-email:willi@nose.net
tech-contact-individual:Y
tech-contact-fname:willi

tech-contact-lname:nose
tech-contact-address-1:horsefair mews
tech-contact-city:romsey
tech-contact-postal-code:4711
tech-contact-country:DE
tech-contact-phone:44 13383794 504040
billing-contact-email:isp@greatone.net
billing-contact-individual:Y
billing-contact-fname:gonzo
billing-contact-lname:nose
billing-contact-address-1:Melrose Plase
billing-contact-postal-code:4711
billing-contact-city:romsey
billing-contact-country:DE
billing-contact-phone:44 13383794 504040
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 2: create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-handle:C123123
admin-contact-handle:C123124
tech-contact-handle:C123125
billing-contact-handle:C123126
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Example 3: create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu
domains1:minus-10a.eu
domains2:minus-10b.eu
domains3:minus-10c.eu
domains4:minus-10d.eu
domains5:minus-10e.eu
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose

owner-contact-fname:hans
owner-contact-address-1:horsefair mews
owner-contact-city:romsey
owner-contact-postal-code:4711
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:same-as-tech-contact
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2

Modify a domain

Introduction

renew <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s),
- the renewalperiod or the desired expiryyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to

check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

Request fields

mailsubject: renew <tld>-domain [your reference id]

Definition of this request

You have to provide the domain name and the renewal period or the desired expire year using the format "YYYY" on one line. You have to separate each field with a ":" (ASCII 058). The maximum for the renewal period is 9 years.

request-field	valid values	required
domains[0..500]	[a-z0-9-]{1,63}\.<tld>:([1-9])\d{4}	yes

.COM renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:4

domains1:minus-119.com:4

domains2:minus-129.com:4

domains3:minus-139.com:4

domains4:minus-149.com:4

Example 3: renew 5 domains for different years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

domains1:minus-119.com:2
domains2:minus-129.com:3
domains3:minus-139.com:4
domains4:minus-149.com:5

Example 4: renew 1 domain using the field expirationyear

subject: renew com-domain [your reference id]

domains0:minus-109.com:2005

.NET Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:4
domains1:minus-119.net:4
domains2:minus-129.net:4
domains3:minus-139.net:4
domains4:minus-149.net:4

Example 3: renew 5 domains for different years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1
domains1:minus-119.net:2
domains2:minus-129.net:3
domains3:minus-139.net:4
domains4:minus-149.net:5

Example 4: renew 1 domain using the field expirationyear

subject: renew net-domain [your reference id]

domains0:minus-109.net:2005

.ORG Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:4

domains1:minus-119.org:4

domains2:minus-129.org:4

domains3:minus-139.org:4

domains4:minus-149.org:4

Example 3: renew 5 domains for different years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

domains1:minus-119.org:2

domains2:minus-129.org:3

domains3:minus-139.org:4

domains4:minus-149.org:5

Example 4: renew 1 domain using the field expirationyear

subject: renew org-domain [your reference id]

domains0:minus-109.org:2005

.INFO Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:4

domains1:minus-119.info:4

domains2:minus-129.info:4

domains3:minus-139.info:4

domains4:minus-149.info:4

Example 3: renew 5 domains for different years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

domains1:minus-119.info:2

domains2:minus-129.info:3

domains3:minus-139.info:4

domains4:minus-149.info:5

Example 4: renew 1 domain using the field expirationyear

subject: renew info-domain [your reference id]

domains0:minus-109.info:2005

.BIZ Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:4

domains1:minus-119.biz:4

domains2:minus-129.biz:4

domains3:minus-139.biz:4

domains4:minus-149.biz:4

Example 3: renew 5 domains for different years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1

domains1:minus-119.biz:2

domains2:minus-129.biz:3

domains3:minus-139.biz:4

domains4:minus-149.biz:5

Example 4: renew 1 domain using the field expirationyear

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:2005

.NAME Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:4
domains1:minus-119.name:4
domains2:minus-129.name:4
domains3:minus-139.name:4
domains4:minus-149.name:4

Example 3: renew 5 domains for different years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1
domains1:minus-119.name:2
domains2:minus-129.name:3
domains3:minus-139.name:4
domains4:minus-149.name:5

Example 4: renew 1 domain using the field expirationyear

subject: renew name-domain [your reference id]

domains0:minus-109.name:2005

.US Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:4
domains1:minus-119.us:4
domains2:minus-129.us:4
domains3:minus-139.us:4
domains4:minus-149.us:4

Example 3: renew 5 domains for different years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

domains1:minus-119.us:2

domains2:minus-129.us:3

domains3:minus-139.us:4

domains4:minus-149.us:5

Example 4: renew 1 domain using the field expire year

subject: renew us-domain [your reference id]

domains0:minus-109.net:2005

.DE Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:4

domains1:minus-119.de:4

domains2:minus-129.de:4

domains3:minus-139.de:4

domains4:minus-149.de:4

Example 3: renew 5 domains for different years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1
domains1:minus-119.de:2
domains2:minus-129.de:3
domains3:minus-139.de:4
domains4:minus-149.de:5

Example 4: renew 1 domain using the field expirationyear

subject: renew de-domain [your reference id]

domains0:minus-109.de:2005

.CN Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:4
domains1:minus-119.cn:4
domains2:minus-129.cn:4
domains3:minus-139.cn:4
domains4:minus-149.cn:4

Example 3: renew 5 domains for different years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1
domains1:minus-119.cn:2
domains2:minus-129.cn:3
domains3:minus-139.cn:4
domains4:minus-149.cn:5

Example 4: renew 1 domain using the field expire year

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:2005

Renew a domain

Introduction

renew <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s),
- the renewalperiod or the desired expiryyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

Request fields

mailsubject: renew <tld>-domain [your reference id]

Definition of this request

You have to provide the domain name and the renewal period or the desired expire year using the format "YYYY" on one line. You have to separate each field with a ":" (ASCII 058). The maximum for the renewal period is 9 years.

request-field	valid values	required
domains[0..500]	[a-z0-9-]{1,63}\.<tld>:([1-9])\d{4}	yes

.COM renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:4

domains1:minus-119.com:4

domains2:minus-129.com:4

domains3:minus-139.com:4

domains4:minus-149.com:4

Example 3: renew 5 domains for different years using the field period

subject: renew com-domain [your reference id]

domains0:minus-109.com:1

domains1:minus-119.com:2

domains2:minus-129.com:3

domains3:minus-139.com:4

domains4:minus-149.com:5

Example 4: renew 1 domain using the field expirationyear

subject: renew com-domain [your reference id]

domains0:minus-109.com:2005

.NET Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:4

domains1:minus-119.net:4

domains2:minus-129.net:4

domains3:minus-139.net:4

domains4:minus-149.net:4

Example 3: renew 5 domains for different years using the field period

subject: renew net-domain [your reference id]

domains0:minus-109.net:1

domains1:minus-119.net:2

domains2:minus-129.net:3

domains3:minus-139.net:4

domains4:minus-149.net:5

Example 4: renew 1 domain using the field expirationyear

subject: renew net-domain [your reference id]

domains0:minus-109.net:2005

.ORG Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:4

domains1:minus-119.org:4

domains2:minus-129.org:4

domains3:minus-139.org:4

domains4:minus-149.org:4

Example 3: renew 5 domains for different years using the field period

subject: renew org-domain [your reference id]

domains0:minus-109.org:1

domains1:minus-119.org:2

domains2:minus-129.org:3

domains3:minus-139.org:4

domains4:minus-149.org:5

Example 4: renew 1 domain using the field expirationyear

subject: renew org-domain [your reference id]

domains0:minus-109.org:2005

.INFO Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:4

domains1:minus-119.info:4

domains2:minus-129.info:4

domains3:minus-139.info:4

domains4:minus-149.info:4

Example 3: renew 5 domains for different years using the field period

subject: renew info-domain [your reference id]

domains0:minus-109.info:1

domains1:minus-119.info:2

domains2:minus-129.info:3

domains3:minus-139.info:4

domains4:minus-149.info:5

Example 4: renew 1 domain using the field expirationyear

subject: renew info-domain [your reference id]

domains0:minus-109.info:2005

.BIZ Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:4
domains1:minus-119.biz:4
domains2:minus-129.biz:4
domains3:minus-139.biz:4
domains4:minus-149.biz:4

Example 3: renew 5 domains for different years using the field period

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:1
domains1:minus-119.biz:2
domains2:minus-129.biz:3
domains3:minus-139.biz:4
domains4:minus-149.biz:5

Example 4: renew 1 domain using the field expirationyear

subject: renew biz-domain [your reference id]

domains0:minus-109.biz:2005

.NAME Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:4

domains1:minus-119.name:4
domains2:minus-129.name:4
domains3:minus-139.name:4
domains4:minus-149.name:4

Example 3: renew 5 domains for different years using the field period

subject: renew name-domain [your reference id]

domains0:minus-109.name:1
domains1:minus-119.name:2
domains2:minus-129.name:3
domains3:minus-139.name:4
domains4:minus-149.name:5

Example 4: renew 1 domain using the field expirationyear

subject: renew name-domain [your reference id]

domains0:minus-109.name:2005

.US Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:4
domains1:minus-119.us:4
domains2:minus-129.us:4
domains3:minus-139.us:4
domains4:minus-149.us:4

Example 3: renew 5 domains for different years using the field period

subject: renew us-domain [your reference id]

domains0:minus-109.us:1

domains1:minus-119.us:2

domains2:minus-129.us:3

domains3:minus-139.us:4

domains4:minus-149.us:5

Example 4: renew 1 domain using the field expire year

subject: renew us-domain [your reference id]

domains0:minus-109.net:2005

.DE Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:4

domains1:minus-119.de:4

domains2:minus-129.de:4

domains3:minus-139.de:4

domains4:minus-149.de:4

Example 3: renew 5 domains for different years using the field period

subject: renew de-domain [your reference id]

domains0:minus-109.de:1

domains1:minus-119.de:2
domains2:minus-129.de:3
domains3:minus-139.de:4
domains4:minus-149.de:5

Example 4: renew 1 domain using the field expirationyear

subject: renew de-domain [your reference id]

domains0:minus-109.de:2005

.CN Renewal

Example 1: renew 1 domain for 1 year using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1

Example 2: renew 5 domains for 4 years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:4
domains1:minus-119.cn:4
domains2:minus-129.cn:4
domains3:minus-139.cn:4
domains4:minus-149.cn:4

Example 3: renew 5 domains for different years using the field period

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:1
domains1:minus-119.cn:2
domains2:minus-129.cn:3
domains3:minus-139.cn:4
domains4:minus-149.cn:5

Example 4: renew 1 domain using the field expire year

subject: renew cn-domain [your reference id]

domains0:minus-109.cn:2005

Transfer a domain

Introduction

transfer <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can transfer a domain from 1 registrar to Joker.com.

You have to provide the following information within the request:

- the domain name,
- the auth-id,
- the billing-contact-handle,

You can transfer 1 com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we don't need information about the owner-contact. We will detect this information from the whois of the current registrar and we will create the contact-handle for the owner-contact automatically.

You need to provide us with a so called auth-id. You have to ask the current registrar for this auth-id. If you provide an invalid auth-id, the transfer will be declined by the current registrar.

As you can see, we need the billing-contact-handle. **We recommend using a billing-handle with the email-address of your "robot-email". If you use a contact-handle with a different e-mail than your robot e-mail, you can't administer the transferred domain using the webinterface and the person with access to the email, which is shown in the provided billing-handle will have access using the web-interface.**

If you don't have a com-contact-handle with your "robot-email", you have to create a com-handle using the "create com-contact" request.

We do not need information about the nameservers. This information will be detected from the whois of the current registrar and we will create the nameservers if necessary.

This procedure implies, that an owner change or change of nameservers during the transfer-process is not possible.

Request fields

mailsubject: transfer <tld>-domain [your reference id]

ATTENTION:

You can transfer 1 domain with one request.

Definition of this request

request-field	valid values	required
domains0	[a-z0-9-]{1,63}\.<tld>	yes
auth-id	.*	yes
billing-contact-handle	Please, refer to the table below.	yes

tld	billing-contact-handle
com	@comcont
net	@netcont
org	@orgcont
info	@infocont
biz	@bizcont
mobi	@mobicont

name	@namecont
us	@uscont
de	@decont
cn	@cncont
eu	@eucont

TRANSFER COM DOMAIN

Example 1: transfer com-domain

subject: transfer com-domain [your reference id]
domains0:minus-109.com
auth-id:0293XaAdA
billing-contact-handle:CCOM-1234

TRANSFER NET DOMAIN

Example 1: transfer net-domain

subject: transfer net-domain [your reference id]

domains0:minus-109.net
auth-id:0293XaAdA
billing-contact-handle:CNET-1234

TRANSFER ORG DOMAIN

Example 1: transfer org-domain

subject: transfer org-domain [your reference id]

domains0:minus-109.org
auth-id:0293XaAdA
billing-contact-handle:CORG-1234

TRANSFER INFO DOMAIN

Example 1: transfer info-domain

subject: transfer info-domain [your reference id]

domains0:minus-109.info

auth-id:0293XaAdA
billing-contact-handle:C176269-LRMS

TRANSFER BIZ DOMAIN

Example 1: transfer biz-domain

subject: transfer biz-domain [your reference id]

domains0:minus-109.biz
auth-id:0293XaAdA
billing-contact-handle:CNEU-123

TRANSFER NAME DOMAIN

Example 1: transfer name-domain

subject: transfer name-domain [your reference id]

domains0:minus-109.name
auth-id:0293XaAdA
billing-contact-handle:CNAM-1234

TRANSFER US DOMAIN

Example 1: transfer us-domain

subject: transfer us-domain [your reference id]

domains0:minus-109.us
auth-id:0293XaAdA
billing-contact-handle:COUS-1234

TRANSFER DE DOMAIN

Example 1: transfer de-domain

subject: transfer de-domain [your reference id]

domains0:minus-109.de
auth-id:0293XaAdA
billing-contact-handle:CODE-1234

TRANSFER CN DOMAIN

Example 1: transfer cn-domain

subject: transfer cn-domain [your reference id]

domains0:minus-109.cn

auth-id:0293XaAdA

billing-contact-handle:COCN-1234

Delete a domain

Introduction

With this request you can delete a domain at Joker.com.

You have to provide the following information within the request:

- domain name(s),
- the special flag force

ATTENTION:

If you delete a domain within the first 72 hours after the registration, the registration-fee will be refunded to your account.

If Joker.com receives the delete-request more than 72 hours after the registration, you have to provide the flag "force:1", in order to accept that the registration-fee will not be refunded to your account. If you do not send the "force:1" in such a case, the request will be rejected.

Request fields

mailsubject: delete domain [your reference id]

Definition of this request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

request-field	valid values	required
tld	(com net org info biz mobi name de cn eu us)	yes
sld	[a-z0-9-]{1,63}	yes
force	1 0	no

DELETE COM DOMAIN

Example 1: delete a domain during the first 72 hours after registration

subject: delete domain [your reference id]

tld:com
sld:frezel

Example 2: delete a domain after the first 72 hours after registration

subject: delete domain [your reference id]

tld:com
sld:frezel
force:1

Example 3: delete a domain only for the case that a refund is possible!

subject: delete domain [your reference id]

tld:com
sld:frezel
force:0

List domains

Introduction

list domains

With this request you can get a list (lexicographically sorted) of all the domains, you have currently registered at joker.com.

You have to provide the target-registry within the request:

```
cno = .com/.net
com = .net
net = .net
org = .org
info = .info
biz = .biz
mobi = .mobi
name = .mobi
de = .de
cn = .cn
eu = .eu
us = .us
```

LIMITATIONS:

- Only 20.000 domains are listed. If you have more than 20.000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20.000 domains at joker.com under 1 registry, this request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

Request fields

mailsubject: list domains [your reference id]

Definition of this request:

request-field	valid values	required
target	com net org info mobi name biz de cn eu us	yes

LIST DOMAINS

Example 1: list domains for .com-domains

subject: list domains [your reference id]

target:com

Example 2: list domains for .net-domains

subject: list domains [your reference id]

target:net

Example 3: list domains for .org-domains

subject: list domains [your reference id]

target:org

Example 4: list domains for .info-domains

subject: list domains [your reference id]

target:info

Example 5: list domains for .biz-domains

subject: list domains [your reference id]

target:biz

Example 6: list domains for .de-domains

subject: list domains [your reference id]

target:de

Example 7: list domains for .cn-domains

subject: list domains [your reference id]

target:cn

Lock a domain

Introduction

lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer-request from a foreign registrar will be declined.

You have to provide the following information within the request:

- domain name

You can lock 1 domain with one request.

Request fields

mailsubject: lock domain [your reference id]

Definition of this request

request-field	valid values	required
fqdn	@fqdn	yes

Example 1: lock a domain

subject: lock domain [your reference id]

fqdn:minus-109.com

Unlock a domain

Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following informations within the request:

- domain name

You can unlock 1 domain with one request.

Request fields

mailsubject: unlock domain [your reference id]

Definitions of this request

request-field	valid values	required
fqdn	@fqdn	yes

Example 1: unlock a domain

subject: unlock domain [your reference id]

fqdn:minus-109.com

Get Auth-id

Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLD's .org/.info/.biz.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

Request fields

mailsubject: get auth-id [your reference id]

Definition of this request

request-field	valid values						required
fqdn	@orgdom	@infodom	@bizdom	@cndom	@eudom	@usdom	yes

Example 1: retrieve the auth-id for a .org-domain

subject: get auth-id [your reference id]

fqdn:minus-109.org

Example 2: retrieve the auth-id for a .biz-domain

subject: get auth-id [your reference id]

fqdn:minus-109.biz

Example 3: retrieve the auth-id for a .eu-domain

subject: get auth-id [your reference id]

fqdn:minus-109.eu

Grant Roles/Domain Permissions, Internal Transfer

Introduction

With this request you can assign 'Roles' (permissions) of domains to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user. In this case, the domain is assigned to the receiving account, including all rights and permissions on this domain.

There are two variants to use this functionality: If the user id (Joker.com user account id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (=> Transfer). This can also be used for users which do not yet have a Joker.com account.

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "reseller id" - must match the 'destination client email')
- desired role (type of permission you want to assign to "client email" resp. "client id" - one of "admin|tech|billing|creator"; "creator" means "all permissions" and is equivalent to an **internal transfer** or 'assignment' - also see 'roles ')

Request fields

mailsubject: joker-internal-transfer [your reference id]

Definition of this request

Valid values for <tld>: **all** Joker.com tlds

request-field	valid values	required
fqdn	[a-z0-9-]{1,63}\.<tld>	yes
destination-client-email	@email	yes
destination-client-id	[0-9]+	no
desired-role	admin tech billing creator (if omitted, default is 'creator')	no

Example 1: assign 'billing'-role to user 123456 (direct)

subject: joker-internal-transfer [your reference id]

body:
fqdn:exampledomain.com
destination-client-email:example-user@gmail.com
destination-client-id:123456
desired-role:billing

Example 2: assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: joker-internal-transfer [your reference id]

body:

fqdn:exampledomain.com

destination-client-email:example-user@gmail.com

desired-role:creator

Revision #1

Created 25 September 2023 11:51:19 by Admin

Updated 5 October 2023 09:00:31 by Admin