

# Nameservers

## Create a nameserver

### Introduction

create <tld>-ns

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

With this request you can create an entry for a nameserver in the Joker.com database. If a nameserver is created, you can reference this nameserver using the hostname during a "create order"-request.

### ATTENTION:

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whois-output.

If you submit a "create-ns"-request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, the values for the ip-addresses are ignored.

### Request fields

mailsubject: create <tld>-ns [your reference id]

request-field	valid values	required
ns-domain-name	([a-z0-9-]{1,63}\.)+(@country com net org info edu mil biz name)	yes

ns-ip-address	@ip	yes
---------------	-----	-----

## CREATE COM NAMESERVER

Example 1: create com-ns

subject: create com-ns [your reference id]

ns-domain-name:ns1.dummy.com

ns-ip-address:194.111.43.1

## CREATE NET NAMESERVER

Example 1: create net-ns

subject: create net-ns [your reference id]

ns-domain-name:ns1.dummy.net

ns-ip-address:194.111.43.1

## CREATE ORG NAMESERVER

Example 1: create org-ns

subject: create org-ns [your reference id]

ns-domain-name:ns1.dummy.org

ns-ip-address:194.111.43.1

## CREATE INFO NAMESERVER

Example 1: create info-ns

subject: create info-ns [your reference id]

ns-domain-name:ns1.dummy.info

ns-ip-address:194.111.43.1

## CREATE BIZ NAMESERVER

Example 1: create biz-ns

subject: create biz-ns [your reference id]

ns-domain-name:ns1.dummy.biz

ns-ip-address:194.111.43.1

CREATE NAME NAMESERVER

Example 1: create name-ns

subject: create name-ns [your reference id]

ns-domain-name:ns1.dummy.name

ns-ip-address:194.111.43.1

CREATE US NAMESERVER

Example 1: create us-ns

subject: create us-ns [your reference id]

ns-domain-name:ns1.dummy.us

ns-ip-address:194.111.43.1

CREATE DE NAMESERVER

Example 1: create de-ns

subject: create de-ns [your reference id]

ns-domain-name:ns1.dummy.de

ns-ip-address:194.111.43.1

CREATE CN NAMESERVER

Example 1: create cn-ns

subject: create cn-ns [your reference id]

ns-domain-name:ns1.dummy.cn

ns-ip-address:194.111.43.1

CREATE EU NAMESERVER

Example 1: create eu-ns

subject: create eu-ns [your reference id]

ns-domain-name:ns1.dummy.net

ns-ip-address:194.111.43.1

# Modify a nameserver

## Introduction

modify <tld>-ns

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

With this request you can change the ip-address of a nameserver in the Joker.com database.

## ATTENTION:

Only nameservers, which Joker.com is responsible for, will be shown with the ip-address in the whois-output, so only these nameservers could be changed.

If you submit a "modify-ns"-request for a nameserver under a domain, which is not registered with Joker.com or for a nameserver under a country-code-domain, this request will be ignored.

## Request fields

mailsubject: modify <tld>-ns [your reference id]

Definition of this request

request-field	valid values	required
ns-handle	([a-z0-9-]{1,63}\.)( @country com net org int edu mil biz info mobi name)	yes
ns-ip-address	@ip	yes

## MODIFY COM NAMESERVER

### Example 1:

modify com-ns

subject: modify com-ns [your reference id]

ns-handle:ns1.dummy.com

ns-ip-address:194.111.43.1

## MODIFY NET NAMESERVER

### Example 1:

modify net-ns

subject: modify com-ns [your reference id]

ns-handle:ns1.dummy.com

ns-ip-address:194.111.43.1

## MODIFY ORG NAMESERVER

### Example 1:

modify org-ns

subject: modify org-ns [your reference id]

ns-handle:ns1.dummy.org  
ns-ip-address:194.111.43.1

## MODIFY INFO NAMESERVER

### Example 1:

modify info-ns

subject: modify info-ns [your reference id]

ns-handle:ns1.dummy.info  
ns-ip-address:194.111.43.1

## MODIFY BIZ NAMESERVER

### Example 1:

modify biz-ns

subject: modify biz-ns [your reference id]

ns-handle:ns1.dummy.biz ns-ip-address:194.111.43.1

## MODIFY NAME NAMESERVER

### Example 1:

modify name-ns

subject: modify name-ns [your reference id]

ns-handle:ns1.dummy.name  
ns-ip-address:194.111.43.1

## MODIFY US NAMESERVER

### Example 1:

modify us-ns  
subject: modify us-ns [your reference id]

ns-handle:ns1.dummy.us  
ns-ip-address:194.111.43.1  
MODIFY DE NAMESERVER

**Example 1:**

modify de-ns

subject: modify de-ns [your reference id]  
ns-handle:ns1.dummy.de  
ns-ip-address:194.111.43.1  
MODIFY CN NAMESERVER

**Example 1:**

modify cn-ns  
subject: modify cn-ns [your reference id]  
ns-handle:ns1.dummy.cn  
ns-ip-address:194.111.43.1

MODIFY EU NAMESERVER

**Example 1:**

modify eu-ns

subject: modify eu-ns [your reference id]  
ns-handle:ns1.dummy.com  
ns-ip-address:194.111.43.1

---

Revision #1

Created 25 September 2023 11:51:53 by Admin

Updated 5 October 2023 09:00:31 by Admin