

# Contacts

## Create a contact

### Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu

With this request you can create person contacts. You can create 1 contact with one request.

### ATTENTION:

You will find the request-field "individual" within the request-definition. if you set it to "Y", you have to provide the request-fields "lname" and "fname" or "name". If you set it to "N", you have to provide information in the request-field "organization".

As the whois for .com shows a field called person, the rules for generating this field are the following:

If you provide the field "name", the whois is showing always the values of this field, regardless of "fname" and "lname".

If you only provide the field "fname" and the field "lname", we will generate the field "name" as the result of the concatenation of "fname" + " " + "lname".

The result of "create com-contact" is a reference which is following the format:

- CCOM-<number> e.g. CCOM-176269 for a .com domain.
- CNET-<number> e.g. CNET-176269 for a .net domain.
- CORG-<number> e.g. CORG-176269 for a .org domain.
- C<number>-LRMS e.g. C176269-LRMS for a .info domain.
- CNEU-<number> e.g. CNEU-176269 for a .biz domain.
- COMO-<number> e.g. COMO-176269 for a .mobi domain.
- CNAM-<number> e.g. CNAM-176269 for a .name domain.
- COUS-<number> e.g. COUS-176269 for a .us domain.
- CODE-<number> e.g. CODE-176269 for a .de domain.
- COCN-<number> e.g. COCN-176269 for a .cn domain.
- C<number> e.g. C176269 for a .eu domain.

## Request fields

mailsubject: create <tld>-contact [your reference id]

Definition of this request

## ATTENTION

According to the rules of DENIC, you have to provide a faxnumber for the admin-c and the tech-c of a **.de** domain.

request-field	valid values		required
	com net org info mobi name us de	biz cn eu	
individual	[YN]		yes
lname	[x20-x7e]{0,80}	[x20-x7e]{0,30}	yes, if individual = Y
fname	[x20-x7e]{0,80}	[x20-x7e]{0,30}	yes, if individual = Y
name	[x20-x7e]{0,80}	[x20-x7e]{0,30}	yes, if fname <b>and/or</b> lname are not given
title	[x20-x7e]{0,80}	[x20-x7e]{0,30}	no
organization	[x20-x7e]{0,80}	[x20-x7e]{0,30}	yes, if individual = N
address-1	[x20-x7e]{1,80}	[x20-x7e]{1,30}	yes
address-2	[x20-x7e]{0,80}	[x20-x7e]{0,30}	no
address-3	Only for biz/cn/eu	[x20-x7e]{0,30}	no
postal-code	[x20-x7e]{1,50}	[x20-x7e]{1,10}	yes

city	[\x20-\x7e]{1,80}	[\x20-\x7e]{1,30}	yes
state	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
country	@country		yes
email	@email		yes
phone	[\x20-\x7e]{1,50}	[[\x20-\x7e]{1,17}	yes
fax	[[\x20-\x7e]{0,50}	[[\x20-\x7e]{0,17}	yes (for admin-c and tech-c of .de only)

## CREATE COM CONTACT

Example 1: create com-contact (name will be generated from fname and lname)

subject: create com-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

Example 2: create com-contact (fname and lname will be ignored)

subject: create com-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## CREATE NET CONTACT

Example 1: create net-contact (name will be generated from fname and lname)

subject: create net-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

Example 2: create net-contact (fname and lname will be ignored)

subject: create net-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## CREATE ORG CONTACT

**Example 1:** create org-contact (name will be generated from fname and lname)

subject: create org-contact [your reference id]

email:gonzo@nose.org  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews

address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

**Example 2:** create org-contact (fname and lname will be ignored)

subject: create org-contact [your reference id]

email:gonzo@nose.org  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CREATE INFO CONTACT

**Example 1:** create info-contact (name will be generated from fname and lname)

subject: create info-contact [your reference id]

email:gonzo@nose.info  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

**Example 2:** create info-contact (fname and lname will be ignored)

subject: create info-contact [your reference id]

email:gonzo@nose.info  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CREATE BIZ CONTACT

**Example 1:** create biz-contact (name will be generated from fname and lname)

subject: create biz-contact [your reference id]

email:gonzo@nose.biz  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

**Example 2:** create biz-contact (fname and lname will be ignored)

subject: create biz-contact [your reference id]

email:gonzo@nose.biz  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## CREATE NAME CONTACT

**Example 1:** create name-contact (name will be generated from fname and lname)

subject: create name-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

**Example 2:** create name-contact (fname and lname will be ignored)

subject: create name-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## CREATE US CONTACT

**Example 1:** create us-contact (name will be generated from fname and lname)

subject: create us-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews

address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

**Example 2:** create us-contact (fname and lname will be ignored)

subject: create us-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CREATE DE CONTACT

**Example 1:** create de-contact (name will be generated from fname and lname)

subject: create de-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
address-1:Musterstrasse 19  
address-2:App. 1  
postal-code:4711  
city:Musterstadt  
country:DE  
phone:49 13383794 504040

**Example 2:** create net-contact (fname and lname will be ignored)

subject: create net-contact [your reference id]



email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:Musterstrasse 19  
address-2:App. 1  
postal-code:4711  
city:Musterstadt  
country:DE  
phone:49 13383794 504040

CREATE CN CONTACT

**Example 1:** create cn-contact (name will be generated from fname and lname)

subject: create cn-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

**Example 2:** create cn-contact (fname and lname will be ignored)

subject: create cn-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## CREATE EU CONTACT

**Example 1:** create eu-contact (name will be generated from fname and lname)

subject: create eu-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

**Example 2:** create eu-contact (fname and lname will be ignored)

subject: create eu-contact [your reference id]

email:gonzo@nose.net  
individual:Y  
fname:gonzo  
lname:nose  
name:Mr. Gonzo Nose  
address-1:horsefair mews  
address-2:App. 1  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

# Modify a contact

## Introduction

With this request you can modify person contacts. You can modify 1 contact with one request. Unspecified request-fields will be ignored.

### ATTENTION:

After changing the content of the specified contact, the whois information is automatically updated.

Keep in mind that you have to provide the numerical suffix of a handle.

- If you want to make an address change within the owner-record of a domain, you have to send a "modify com-domain"-request after changing the content of the specified handle.
- Only contact-handles, which are created by the reseller or where the e-mail within the contact is matching the reseller's robot-email can be changed.

#### Definition of this request

request-field	valid values		required
	com net org info mobi name us de	biz cn eu	
handle	Please, refer to the table below.		yes
individual	[YN]		yes
lname	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no, if name is given
fname	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no, if name is given
name	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	yes, if fname <b>and/or</b> lname are not given
title	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
organization	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	yes, if individual = N
address-1	[\x20-\x7e]{1,80}	[\x20-\x7e]{1,30}	yes
address-2	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
address-3	Only for biz/cn/eu	[\x20-\x7e]{0,30}	no
postal-code	[\x20-\x7e]{1,50}	[\x20-\x7e]{1,10}	yes
city	[\x20-\x7e]{1,80}	[\x20-\x7e]{1,30}	yes
state	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
country	@country		yes
email	@email		yes
phone	[\x20-\x7e]{1,50}	[[\x20-\x7e]{1,17}	yes
fax	[[\x20-\x7e]{0,50}	[[\x20-\x7e]{0,17}	yes (for admin-c and tech-c of .de only)

TLD	handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>

## MODIFY COM CONTACT

### **Example 1:** modify com-contact

subject: modify com-contact [your reference id]

handle:CCOM-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## MODIFY NET CONTACT

### **Example 1:** modify net-contact

subject: modify net-contact [your reference id]

handle:CNET-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE

phone:44 13383794 504040

## MODIFY ORG CONTACT

### **Example 1:** modify org-contact

subject: modify org-contact [your reference id]

handle:CORG-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## MODIFY INFO CONTACT

### **Example 1:** modify info-contact

subject: modify info-contact [your reference id]

handle:C293829-LRMS  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

### **Example 2:** modify info-contact (new naming convention for info-handles)

subject: modify info-contact [your reference id]

handle:CAFI-007  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## MODIFY BIZ CONTACT

**Example 1:** modify biz-contact

subject: modify biz-contact [your reference id]

handle:CNEU-12345  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

MODIFY NAME CONTACT

**Example 1:** modify name-contact

subject: modify name-contact [your reference id]

handle:CNAM-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

MODIFY US CONTACT

**Example 1:** modify us-contact

subject: modify us-contact [your reference id]

handle:COUS-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

MODIFY DE CONTACT

**Example 1:** modify de-contact

subject: modify de-contact [your reference id]

handle:CODE-1235

address-1:Musterstrasse 1

postal-code:47011

city:Musterstadt

country:DE

phone:44 13383794 504040

MODIFY EU CONTACT

### **Example 1:** modify eu-contact

subject: modify eu-contact [your reference id]

handle:C12345

address-1:horsefair mews

postal-code:4711

city:romsey

country:DE

phone:44 13383794 504040

# Change an address

## Introduction

change <tld>-address

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn

With this request you can change the address of the domain owner.

## ATTENTION:

It is not possible to change the following fields of the owner-record:

- individual
- lname
- fname
- title
- organization
- email

### Request fields

mailsubject: change com-address [your reference id]

Definition of this request

request-field	valid values		required
	com net org info mobi name us de	biz cn	
domains0	[a-z0-9-]{1,63}\.<tld>		yes
address-1	[\x20-\x7e]{1,80}	[\x20-\x7e]{1,30}	no
address-2	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
address-3	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
postal-code	[\x20-\x7e]{1,50}	[\x20-\x7e]{0,30}	no
city	[\x20-\x7e]{1,80}	[\x20-\x7e]{1,30}	no
state	[\x20-\x7e]{0,80}	[\x20-\x7e]{0,30}	no
country	@country		no
phone	[[\x20-\x7e]{1,50}	[[\x20-\x7e]{1,17}	no
fax	[[\x20-\x7e]{0,50}	[[\x20-\x7e]{0,17}	no

### CHANGE .COM ADDRESS

**Example 1:** change com-address



subject: change com-address [your reference id]

domains0:gonzo.com  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .NET ADDRESS

**Example 1:** change net-address

subject: change net-address [your reference id]

domains0:gonzo.net  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .ORG ADDRESS

**Example 1:** change org-address

subject: change org-address [your reference id]

domains0:gonzo.org  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .INFO ADDRESS

**Example 1:** change info-address

subject: change info-address [your reference id]

domains0:gonzo.info  
address-1:horsefair mews  
postal-code:4711

city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .BIZ ADDRESS

**Example 1:** change biz-address

subject: change biz-address [your reference id]

domains0:gonzo.biz  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .NAME ADDRESS

**Example 1:** change name-address

subject: change name-address [your reference id]

domains0:gonzo.name  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .US ADDRESS

**Example 1:** change us-address

subject: change us-address [your reference id]

domains0:gonzo.us  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .DE ADDRESS

### Example 1: change de-address

subject: change de-address [your reference id]

domains0:gonzo.de  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .CN ADDRESS

### Example 1: change cn-address

subject: change cn-address [your reference id]

domains0:gonzo.cn  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

# Change an owner

## Introduction

With this request you can change the owner of a .com/.net/.org/.info/.mobi/.name/.biz/.de/.cn/.eu/.us-domain.

## Request fields

mailsubject: change owner [your reference id]

Definition of this request

request-field	valid values	required
domains0	[a-z0-9-]{1,63}\.(com net org info mobi biz de cn eu us)	yes
email	an email <b>without</b> the numerical suffix	no

individual	[YN]	no
name (.com,.net,.org,.info,.biz,.mobi,.de,.cn,.eu,.us only)	[\x20-\x7e]{0,80}	no
lname	[\x20-\x7e]{0,80}	no
fname	[\x20-\x7e]{0,80}	no
title	[\x20-\x7e]{0,80}	no
organization	[\x20-\x7e]{0,80}	no
address-1	[\x20-\x7e]{0,80}	no
address-2	[\x20-\x7e]{0,80}	no
postal-code	[\x20-\x7e]{0,50}	no
state	[\x20-\x7e]{0,80}	no
city	[\x20-\x7e]{0,80}	no
country	@country	no
phone	[\x20-\x7e]{0,50}	no
fax	[\x20-\x7e]{0,50}	no
lock-opt-out	[YN]	no

## CHANGE .COM OWNER

### Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.com

fname:hans

lname:nose

address-1:horsefair mews

postal-code:4711

city:romsey

country:DE

phone:44 13383794 504040

## CHANGE .NET OWNER

### Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.net  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .ORG OWNER

**Example 1:** change owner

subject: change owner [your reference id]  
domains0:gonzo.org  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .INFO OWNER

**Example 1:** change owner

subject: change owner [your reference id]  
  
domains0:gonzo.info  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .BIZ OWNER

**Example 1:** change owner

subject: change owner [your reference id]  
  
domains0:gonzo.biz

fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .NAME OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.name  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .US OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.us  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .DE OWNER

**Example 1:** change owner

subject: change owner [your reference id]

domains0:gonzo.de

fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

CHANGE .CN OWNER

### Example 1: change owner

subject: change owner [your reference id]

domains0:gonzo.cn  
fname:hans  
lname:nose  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

# .asia Contacts

**new-handle** (implicit creation of a new contact)

This means the definition of a new contact. If a contact with the provided email address exists in the JOKER-DATABASE, a new contact will be created. The reference for the created handle is following the format COAS-  
<number>, e.g. COAS-176269.

### ATTENTION:

The name of the request field depends on the context. If you want to create a contact for the owner-contact, you have to replace the ".." at the beginning of the fieldname with "owner-contact".

If you want to create a contact for the admin-contact, you have to replace the ".." at the beginning of the fieldname with "admin-contact".

If you want to create a contact for the tech-contact, you have to replace the ".." at the beginning of the fieldname with "tech-contact".

If you want to create a contact for the billing-contact, you have to replace the ".." at the beginning of the fieldname with "billing-contact".

There is a new request field called **name** within the contact definition. This field is mandatory, if you do not provide the **fname** and **lname**. You have to provide the request field **name**, if **fname** and **lname** are not found. This is very important for the whois output. Everytime a field **person** is shown. If you are using the request field

name, the whois is showing the value for **name**, regardless the content of the request fields **fname** and **lname**. If you do not provide the request field **name** but your are providing the request fields **fname** and **lname**, the whois is showing the concatenation of these fields.

There is also a new request field called **address-3** within the contact definition. This field is not mandatory, it is simply the 3rd line of the address.

request-field	valid values	required
".."-individual	[YN]	yes
".."-lname	[\x20-\x7e]{0,80}	no, if name is given
".."-fname	[\x20-\x7e]{0,80}	no, if name is given
".."-name	[\x20-\x7e]{0,80}	yes, if fname <b>and/or</b> lname are not given
".."-title	[\x20-\x7e]{0,80}	no
".."-organization	[\x20-\x7e]{0,80}	yes, if individual = N
".."-address-1	[\x20-\x7e]{1,80}	yes
".."-address-2	[\x20-\x7e]{0,80}	no
".."-address-3	[\x20-\x7e]{0,80}	no
".."-postal-code	[\x20-\x7e]{1,50}	yes
".."-city	[\x20-\x7e]{1,80}	yes
".."-state	[\x20-\x7e]{0,80}	no
".."-country	@country	yes
".."-email	@email	yes
".."-phone	[[\x20-\x7e]{1,50}	yes
".."-fax	[[\x20-\x7e]{0,50}	no

**An existing contact** (@asiacont or @same-as) (.asia only)

This means an existing contact handle in the JOKER-DATABASE.

#### Examples:

```
owner-contact-handle:COAS-176269
admin-contact-handle:COAA-176229
tech-contact-handle:COAS-176269
billing-contact-handle:COAS-176269
```

**ASIA-domains require an additional type of contact, the CED contact. This contact has to have its residence in the Asian/Australian area.**

**The Joker.com Registry Gateways automatically will use your provided tech-contact for the CED contact.**

This means that the request for you remains consistent with the usual requests, you only have to make sure



that the country code is correct, otherwise the .asia registry will reject the order.

In case you have entered a non-existing contact handle, the system will send you an errormail.

It is also possible to set a reference to a contact definition, which has been made earlier within the current request. To do so, please use the following syntax:

admin-contact-handle:same-as-owner-contact

tech-contact-handle:same-as-admin-contact

billing-contact-handle:same-as-tech-contact

The **@same-as** makro always replaces the value for the specified contact handle with the email address of the makrotarget. If the referenced contact has to be created with this request, it takes the result handle.

Keep in mind that for .asia-requests the contact handles for (.com/.net/.org/.info/.biz/.de)-contacts are not allowed. If you are referencing to a shortcut like hans@nose.net#1, you will get an error.

---

Revision #5

Created 14 September 2023 11:21:36 by Admin

Updated 29 September 2023 10:06:15 by Admin