

Joker.com FAQ

Table of Content

PHP	2
Read first - important for PHP examples	2
List domains of a customer	3

PHP

Read first - important for PHP examples

Please note that there is full DMAPI based interface written in PHP available. It is free to download and modify, and could be [downloaded from Sourceforge](#).

Please read more at section [Reseller Control Panel](#).

The published examples in PHP are parts of this project and are stripped in terms of functionality and error handling. It is strongly recommended to use the complete code base from Sourceforge.

Keywords: DMAPI, examples, code, php

Last update: 2016-01-13 16:57

PHP

List domains of a customer

```
<?php

//sends HTTP request using CURL

function query_host($conn_server, $params = "", $get_header = false)
{
    $ch = curl_init();
    curl_setopt($ch, CURLOPT_URL, $conn_server.$params);
    if (preg_match("/^https:\\/\\/i", $conn_server)) {
        curl_setopt($ch, CURLOPT_SSL_VERIFYHOST, 0);
        curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, 0);
    }

    curl_setopt($ch, CURLOPT_RETURNTRANSFER, 1);

    if ($get_header) {
        curl_setopt($ch, CURLOPT_HEADER, 1);
    }

    else {
        curl_setopt($ch, CURLOPT_HEADER, 0);
    }

    $result = curl_exec($ch);

    if (curl_errno($ch)) {
        print "curl error";
    }

    else {
        curl_close($ch);
    }

    return $result;
}

//builds query, sends request and gets the answer back

function execute_request($request, $params, &$sessid)
{
    //build the query
    $http_query = "/request/" . $request . "?" . $params . "&auth-sid"
    = ".$sessid."&client-ip=".$_SERVER["REMOTE_ADDR"];
}
```

PHP

```
//send the request
$raw_res = query_host("https://dmapl.joker.com", $http_query, true
);
$temp_arr = @explode("\r\n\r\n", $raw_res, 2);
//split the response for further processing
if (is_array($temp_arr) && 2 == count($temp_arr)) {
    return $temp_arr[1];
}

else {
    return false;
}
}

//basic parsing of the DMAPi header

function parse_response_header($header)
{
    $raw_arr = explode("\n", trim($header));
    $result = array();
    if (is_array($raw_arr)) {
        foreach ($raw_arr as $key => $value)
        {
            $keyval = array();
            if (preg_match("/^([\s]+):\s+(.+)\s*$/", $value, $keyval)
) {
                $sarr[strtolower($keyval[1])] = $keyval[2];
            }

            else {
                print "Header line not parseable - pattern does not ma
tch\nRaw header:\n$value";
            }
        }
    }

    else {
        $sarr = "";
        print "Unidentified error\nRaw header:\n$header";
    }

    return $sarr;
}

//parses the reply from DMAPi into a header and body
function parse_response($res)
{
    $raw_arr = explode("\n\n", trim($res));
    $sarr_elements = count($raw_arr);
```

PHP

```
if ($arr_elements > 0) {
    $temp["response_header"] = parse_response_header($raw_arr["0"]
);
    $temp["response_body"] = $raw_arr["1"];
}

else {
    print "Couldn't split the response into response header and re
sponse body\nRaw result:\n$res";
    $temp = "";
}

return $temp;
}

$response = "";
$authid = "none";
//first obtaining an Auth-ID
$username = "<your username here>";
$password = "<your password here>";
$fields = "username=".urlencode($username)."&password=".urlencode($pas
sword);
$result = execute_request("login", $fields, $authid);
$result = parse_response($result);
$authid = $result["response_header"]["auth-sid"];
if (!$authid) {
    print "no auth-id was obtained - probably due to wrong username or
password";
    exit;
}

//now asking for the domain list
$pattern = "*";
$fields = "pattern=".urlencode($pattern);
$result = execute_request("query-domain-list", $fields, $authid);
$result = parse_response($result);

print_r($result["response_header"]);
print "< br /> ";
print_r($result["response_body"]);
```

PHP

Keywords: DMAPI, examples, code, php

Last update: 2016-01-13 16:58

