

# Joker.com FAQ

## Table of Content

<b>Domains</b> .....	2
Create an order .....	2
Modify a domain .....	26
Renew a domain .....	32
Transfer a domain .....	36
Delete a domain .....	39
List domains .....	41
Lock a domain .....	43
Unlock a domain .....	44
Get Auth-id .....	45
Grant Roles/Domain Permissions, Internal Transfer .....	46

# Domains

## Create an order

### Introduction

create <tld>-order

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
  
- xxx
  
- asia
  
- me

With this request you can register one or more domains.

You have to provide the following information within the request:

- domain name(s),
- owner-contact-handle,
- admin-contact-handle,
- tech-contact-handle,
- billing-contact-handle,
- nameserver information,
- additional services, if required.

You can register up to 501 domains with one request.

If you register more than one domain with a request, all domains registered with this request will have the same contact and nameserver structure.

There are two new requestfields within this request:

- name

# Domains

- address-3

## ATTENTION

Please, refer to the table for the corresponding contact handles.

TLD	Contact handle
com	CCOM-<number>
net	CNET-<number>
org	CORG-<number>
info	C<number>-LRMS
biz	CNEU-<number>
mobi	COMO-<number>
name	CNAM-<number>
us	COUS-<number>
de	CODE-<number>
cn	COCN-<number>
eu	C<number>
me	COME-<number>
asia	COAS-<number>
xxx	CONX-<number>

## Request fields

mailsubject: create <tld>-order [your reference id]

Definition of this request

tld	request field		
	domains[0..500]	period	language[0..500]
com	[a-z0-9]{1,63}\.com	^([1..9]{1})\$	<a href="#">@language</a>
net	[a-z0-9]{1,63}\.net	^([1..9]{1})\$	
org	[a-z0-9]{1,63}\.org	^([1..9]{1})\$	
info	[a-z0-9]{1,63}\.info	^([1..9]{1})\$	
biz	[a-z0-9][a-z0-9]{1,6	^([1..9]{1})\$	

# Domains

	1}[a-z0-9]\.biz		
mobi	[a-z0-9]{1,63}\.mobi	^([1..9]{1})\$	
name	[a-z0-9]{1,63}\.name	^([2..9]{1})\$	
us	[a-z0-9]{1,63}\.us	^([2..9]{1})\$	
de	[a-z0-9]{1,63}\.de	^([1..9]{1})\$	
cn	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.cn	^([1..9]{1})\$	
eu	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.eu	^([1..9]{1})\$	
me	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.me	^([1..9]{1})\$	
asia	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.asia	^([1..9]{1})\$	
xxx	[a-z0-9][a-z0-9]{1,61}[a-z0-9]\.xxx	^([1..9]{1})\$	
required	yes	yes	no (IDN domains only)

tld	owner-contact-handle	admin-contact-handle	tech-contact-handle	billing-contact-handle
com			<a href="#">@comcont</a>	
net			<a href="#">@netcont</a>	
org			<a href="#">@orgcont</a>	
info			<a href="#">@infocont</a>	
biz			<a href="#">@decont</a>	
mobi			<a href="#">@mobicont</a>	
name			<a href="#">@namecont</a>	
us			<a href="#">@uscont</a>	
de			<a href="#">@bizcont</a>	
cn			<a href="#">@cncont</a>	
eu			<a href="#">@eucont</a>	
me			@mecont	
asia			@asiacon	
required			yes	

tld	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle	ns1-handle
<tld>				<a href="#">@ns</a>		
required	yes	yes			no	

# Domains

## .COM order

**Example 1:** create com-order with implicit contact-handle-creation of the owner-contact

subject: create com-order [your reference id]

```
domains0:xn--hans-mller-feb.com
language0:AFR
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create com-order with implicit nameserver-creation

subject: create com-order [your reference id]

```
domains0:minus-109.com
domains1:minus-10a.com
domains2:minus-10b.com
domains3:minus-10c.com
domains4:minus-10d.com
domains5:minus-10e.com
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create com-order with implicit contact-handle-creation of all contacts

# Domains

subject: create com-order [your reference id]

domains0:minus-109.com  
domains1:minus-10a.com  
domains2:minus-10b.com  
domains3:minus-10c.com  
domains4:minus-10d.com  
domains5:minus-10e.com  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**.NET order**

# Domains

**Example 1:** create net-order with implicit contact-handle-creation of the owner-contact

subject: create net-order [your reference id]

```
domains0:xn--hans-mller-feb.net
language0:AFR
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create net-order with implicit nameserver-creation

subject: create net-order [your reference id]

```
domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
domains4:minus-10d.net
domains5:minus-10e.net
period:2
owner-contact-handle:CCOM-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CCOM-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create net-order [your reference id]

```
domains0:minus-109.net
domains1:minus-10a.net
domains2:minus-10b.net
domains3:minus-10c.net
```

# Domains

domains4:minus-10d.net  
domains5:minus-10e.net  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **.ORG order**

**Example 1:** create org-order with implicit contact-handle-creation of the owner-contact

subject: create org-order [your reference id]



# Domains

```
domains0:xn--hans-mller-feb.org
language0:AFR
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:gonzo@nose.net
owner-contact-individual:Y
owner-contact-fname:gonzo
owner-contact-lname:nose
owner-contact-address-1:horsefair mews
owner-contact-postal-code:4711
owner-contact-city:romsey
owner-contact-country:DE
owner-contact-phone:44 13383794 504040
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-123
ns1-handle:ns.gonzo.net
ns2-handle:ns2.gonzo.net
```

**Example 2:** create org-order with implicit nameserver-creation

```
subject: create org-order [your reference id]
```

```
domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-handle:CORG-123
admin-contact-handle:same-as-owner-contact
tech-contact-handle:same-as-admin-contact
billing-contact-handle:CORG-13323
ns1-domain-name:nsxx1.gonzo.net
ns1-ip-address:194.201.101.1
ns2-domain-name:nsxx1.gonzo.net
ns2-ip-address:194.201.101.2
```

**Example 3:** create org-order with implicit contact-handle-creation of all contacts

```
subject: create org-order [your reference id]
```

```
domains0:minus-109.org
domains1:minus-10a.org
domains2:minus-10b.org
domains3:minus-10c.org
domains4:minus-10d.org
domains5:minus-10e.org
period:2
owner-contact-email:hans@nose.net
owner-contact-individual:Y
owner-contact-lname:nose
```

# Domains

owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .INFO order

**Example 1:** create info-order with implicit contact-handle-creation of the owner-contact

subject: create info-order [your reference id]

domains0:xn--hans-mlller-feb.info  
language0:AFR  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2

# Domains

owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:C282828-LRMS  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 2:** create info-order with implicit nameserver-creation

subject: create info-order [your reference id]

domains0:minus-109.info  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2  
owner-contact-handle:C176269-LRMS  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:C176219-LRMS  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **Example 3:** create info-order with implicit contact-handle-creation of all contacts

subject: create info-order [your reference id]

domains0:minus-109.info  
domains1:minus-10a.info  
domains2:minus-10b.info  
domains3:minus-10c.info  
domains4:minus-10d.info  
domains5:minus-10e.info  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y

# Domains

admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## **.BIZ order**

**Example 1:** create biz-order with implicit contact-handle-creation of the owner-contact

domains0:xn--hans-mller-feb.biz  
language0:AFR  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo

# Domains

admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## Example 2: create biz-order with implicit nameserver-creation

subject: create biz-order [your reference id]

domains0:minus-109.biz  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz  
domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-handle:CNEU-123  
admin-contact-handle:CNEU-124  
tech-contact-handle:CNEU-125  
billing-contact-handle:CNEU-126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## Example 3: create biz-order with implicit contact-handle-creation of all contacts

subject: create biz-order [your reference id]

domains0:minus-109.biz  
domains1:minus-10a.biz  
domains2:minus-10b.biz  
domains3:minus-10c.biz

# Domains

domains4:minus-10d.biz  
domains5:minus-10e.biz  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .MOBI ORDER

**Example 1:** create mobi-order with implicit contact-handle-creation of the owner-contact

subject: create mobi-order [your reference id]

domains0:xn--hans-mller-feb.mobi  
language0:AFR  
domains1:minus-10a.mobi

# Domains

domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COMO-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create mobi-order with implicit nameserver-creation

subject: create mobi-order [your reference id]

domains0:minus-109.mobi  
domains1:minus-10a.mobi  
domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-handle:COMO-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COMO-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create mobi-order with implicit contact-handle-creation of all contacts

subject: create mobi-order [your reference id]

domains0:minus-109.mobi  
domains1:minus-10a.mobi  
domains2:minus-10b.mobi  
domains3:minus-10c.mobi  
domains4:minus-10d.mobi  
domains5:minus-10e.mobi  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey

# Domains

owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .NAME ORDER

**Example 1:** create name-order with implicit contact-handle-creation of the owner-contact

subject: create name-order [your reference id]

domains0:xn--hans-mller-feb.net  
language0:AFR  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-email:gonzo@nose.net



# Domains

owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CNAM-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create name-order with implicit nameserver-creation

subject: create name-order [your reference id]

domains0:minus-109.name  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-handle:CNAM-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CNAM-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create name-order with implicit contact-handle-creation of all contacts

subject: create name-order [your reference id]

domains0:minus-109.name  
domains1:minus-10a.name  
domains2:minus-10b.name  
domains3:minus-10c.name  
domains4:minus-10d.name  
domains5:minus-10e.name  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo

# Domains

admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .US ORDER

**Example 1:** create us-order with implicit contact-handle-creation of the owner-contact

subject: create us-order [your reference id]

domains0:xn--hans-mller-feb.us  
language0:AFR  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nose  
owner-contact-address-1:horsefair mews  
owner-contact-postal-code:4711  
owner-contact-city:romsey  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact

# Domains

tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-123  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

## Example 2: create us-order with implicit nameserver-creation

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-handle:COUS-123  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:COUS-13323  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## Example 3: create us-order with implicit contact-handle-creation of all contacts

subject: create us-order [your reference id]

domains0:minus-109.us  
domains1:minus-10a.us  
domains2:minus-10b.us  
domains3:minus-10c.us  
domains4:minus-10d.us  
domains5:minus-10e.us  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi

# Domains

tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .DE ORDER

**Example 1:** create de-order with implicit contact-handle-creation of the owner-contact

subject: create de-order [your reference id]

domains0:minus-10x.de  
language0:GER  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nase  
owner-contact-address-1:Musterstrasse 11  
owner-contact-postal-code:4711  
owner-contact-city:Musterhausen  
owner-contact-country:DE  
owner-contact-phone:49 13383794 504040  
owner-contact-fax:49 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CODE-1007  
ns1-handle:ns.gonzo.net  
ns2-handle:ns2.gonzo.net

**Example 2:** create net-order with implicit nameserver-creation

subject: create de-order [your reference id]

# Domains

domains0:minus-109.de  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-handle:CODE-1007  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:CODE-1007  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create net-order with implicit contact-handle-creation of all contacts

subject: create de-order [your reference id]

domains0:minus-109.de  
domains1:minus-10a.de  
domains2:minus-10b.de  
domains3:minus-10c.de  
domains4:minus-10d.de  
domains5:minus-10e.de  
period:2  
owner-contact-email:gonzo@nose.net  
owner-contact-individual:Y  
owner-contact-fname:gonzo  
owner-contact-lname:nase  
owner-contact-address-1:Musterstrasse 11  
owner-contact-postal-code:4711  
owner-contact-city:Musterhausen  
owner-contact-country:DE  
owner-contact-phone:49 13383794 504040  
owner-contact-fax:49 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nase  
admin-contact-address-1:Musterstrasse 11  
admin-contact-postal-code:4711  
admin-contact-city:Musterhausen  
admin-contact-country:DE  
admin-contact-phone:49 13383794 504040  
admin-contact-fax:49 13383794 504040  
tech-contact-email:gonzo@nose.net  
tech-contact-individual:Y  
tech-contact-fname:gonzo  
tech-contact-lname:nase  
tech-contact-address-1:Musterstrasse 11  
tech-contact-postal-code:4711  
tech-contact-city:Musterhausen  
tech-contact-country:DE  
tech-contact-phone:49 13383794 504040  
tech-contact-fax:49 13383794 504040  
billing-contact-email:gonzo@nose.net

# Domains

billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nase  
billing-contact-address-1:Musterstrasse 11  
billing-contact-postal-code:4711  
billing-contact-city:Musterhausen  
billing-contact-country:DE  
billing-contact-phone:49 13383794 504040  
billing-contact-fax:49 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .CN ORDER

**Example 1:** create cn-order with implicit contact-handle-creation of the owner-contact

subject: create cn-order [your reference id]

domains0:xn--hans-mller-feb.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net

# Domains

billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## Example 2: create cn-order using existing cn-handles

subject: create cn-order [your reference id]

domains0:minus-109.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-handle:COCN-123  
admin-contact-handle:COCN-124  
tech-contact-handle:COCN-125  
billing-contact-handle:COCN-126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## Example 3: create cn-order with backreferences using @same-as

subject: create cn-order [your reference id]

domains0:minus-109.cn  
domains1:minus-10a.cn  
domains2:minus-10b.cn  
domains3:minus-10c.cn  
domains4:minus-10d.cn  
domains5:minus-10e.cn  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net

# Domains

ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

## .EU ORDER

**Example 1:** create eu-order with implicit contact-handle-creation of all contacts

subject: create eu-order [your reference id]

domains0:xn--hans-mller-feb.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-email:gonzo@nose.net  
admin-contact-individual:Y  
admin-contact-fname:gonzo  
admin-contact-lname:nose  
admin-contact-address-1:horsefair mews  
admin-contact-city:romsey  
admin-contact-postal-code:4711  
admin-contact-country:DE  
admin-contact-phone:44 13383794 504040  
tech-contact-email:willi@nose.net  
tech-contact-individual:Y  
tech-contact-fname:willi  
tech-contact-lname:nose  
tech-contact-address-1:horsefair mews  
tech-contact-city:romsey  
tech-contact-postal-code:4711  
tech-contact-country:DE  
tech-contact-phone:44 13383794 504040  
billing-contact-email:isp@greatone.net  
billing-contact-individual:Y  
billing-contact-fname:gonzo  
billing-contact-lname:nose  
billing-contact-address-1:Melrose Plase  
billing-contact-postal-code:4711  
billing-contact-city:romsey  
billing-contact-country:DE  
billing-contact-phone:44 13383794 504040  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1



# Domains

ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 2:** create eu-order using existing .eu-handles

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-handle:C123123  
admin-contact-handle:C123124  
tech-contact-handle:C123125  
billing-contact-handle:C123126  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

**Example 3:** create eu-order with backreferences using @same-as

subject: create eu-order [your reference id]

domains0:minus-109.eu  
domains1:minus-10a.eu  
domains2:minus-10b.eu  
domains3:minus-10c.eu  
domains4:minus-10d.eu  
domains5:minus-10e.eu  
period:2  
owner-contact-email:hans@nose.net  
owner-contact-individual:Y  
owner-contact-lname:nose  
owner-contact-fname:hans  
owner-contact-address-1:horsefair mews  
owner-contact-city:romsey  
owner-contact-postal-code:4711  
owner-contact-country:DE  
owner-contact-phone:44 13383794 504040  
admin-contact-handle:same-as-owner-contact  
tech-contact-handle:same-as-admin-contact  
billing-contact-handle:same-as-tech-contact  
ns1-domain-name:nsxx1.gonzo.net  
ns1-ip-address:194.201.101.1  
ns2-domain-name:nsxx1.gonzo.net  
ns2-ip-address:194.201.101.2

Keywords: create, order, registration

Last update: 2015-07-29 12:02

# Domains

## Modify a domain

### Introduction

modify <tld>-domain

Valid values for <tld>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- de
- cn
- eu
  
- xxx
  
- asia
  
- me

With this request you can modify existing domains. You have to provide the following information within the

# Domains

request:

- the domainname,
- handle(s) you want to change. (handles from the info-system are not valid)

The system will ignore not specified handles, so you have to provide only the handles, you would like to change.

## Changes within the owner-contact

In case of changing the owner-contact-handle, the system checks, if lname and/or fname and/or organization differ from the original owner-contact-handle. If there are differences these changes will be ignored.

## Request fields

mailsubject: modify <tld>-domain [your reference id]

Definition of this request

request-field	valid values		required
tld	com net org info mobi  name us de	biz eu	yes
sld	[a-z0-9-]{1,63}	[a-z0-9][a- z0-9-]{1,61}[a-z0-9]	yes
owner-contact-handle	Please, refer to the table below for the valid values.		no
admin-contact-handle			no
tech-contact-handle			no

# Domains

billing-contact-handle		no
ns1-handle	<a href="#">@ns</a>	no
ns2-handle		no
ns3-handle		no
ns4-handle		no
ns5-handle		no
ns6-handle		no

tld	contact handle
com	<a href="#">@comcont</a>
net	<a href="#">@netcont</a>
org	<a href="#">@orgcont</a>
info	<a href="#">@infocont</a>
biz	<a href="#">@bizcont</a>
mobi	<a href="#">@mobicont</a>
name	<a href="#">@namecont</a>
us	<a href="#">@uscont</a>
de	<a href="#">@decont</a>
cn	<a href="#">@cncont</a>
eu	<a href="#">@eucont</a>

## Example 1: modify com-domain

subject: modify domain [your reference id]

sld:gonzo  
tld:com  
admin-contact-handle:gonzo@nose.com#0  
tech-contact-handle:hans@nose.com  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## Example 2: modify net-domain

subject: modify net-domain [your reference id]

sld:gonzo  
tld:net  
admin-contact-handle:CNET-1234  
tech-contact-handle:CNET-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

# Domains

## **Example 3:** modify org-domain

subject: modify net-domain [your reference id]

sld:gonzo  
tld:org  
admin-contact-handle:CORG-1234  
tech-contact-handle:CORG-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 4:** modify info-domain

subject: modify info-domain [your reference id]

sld:gonzo  
tld:info  
admin-contact-handle:C112234-LRMS  
tech-contact-handle:C112244-LRMS  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

OR

modify info-domain (new naming convention for info-handles)

subject: modify info-domain [your reference id]

sld:gonzo  
tld:info  
admin-contact-handle:C112244-LRMS  
tech-contact-handle:CAFI-007  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 5:** modify biz-domain

subject: modify biz-domain [your reference id]

sld:gonzo  
tld:biz  
admin-contact-handle:CNEU-11224  
tech-contact-handle:CNEU-112244  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 6:** modify mobi-domain

# Domains

subject: modify mobi-domain [your reference id]

sld:gonzo  
tld:mobi  
admin-contact-handle:COMO-1234  
tech-contact-handle:COMO-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 7:** modify name-domain

subject: modify name-domain [your reference id]

sld:gonzo  
tld:name  
admin-contact-handle:CNAM-1234  
tech-contact-handle:CNAM-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 8:** modify us-domain

subject: modify us-domain [your reference id]

sld:gonzo  
tld:us  
admin-contact-handle:COUS-1234  
tech-contact-handle:COUS-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 9:** modify de-domain

subject: modify de-domain [your reference id]

sld:gonzo  
tld:de  
admin-contact-handle:CODE-1234  
tech-contact-handle:CODE-1234  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

## **Example 10:** modify cn-contact

subject: modify cn-contact [your reference id]

# Domains

handle:COCN-1235  
address-1:horsefair mews  
postal-code:4711  
city:romsey  
country:DE  
phone:44 13383794 504040

## **Example 11:** modify eu-domain

subject: modify eu-domain [your reference id]

sld:gonzo  
tld:eu  
admin-contact-handle:C112244  
tech-contact-handle:C112244  
ns1-handle:ns1.gonzo.net  
ns2-handle:ns2.gonzo.net

Keywords: modify-domain, nameserver, contacts

Last update: 2015-07-29 12:02

# Domains

## Renew a domain

Introduction

Renew <ID>-domain

Valid values for <ID>:

- com
- net
- org
- info
- biz
- mobi
- name
- us
- ca
- co

With this request you can renew up to 500 domains at Joker.com.

You have to provide the following information within the request:

- the domainname(s)
- the renewalperiod or the desired expirationyear

You can renew up to 500 domains with one request.

Due to the fact, that you can renew more than 1 domain with one request, the format is a little bit different from the other requests. Please check the given examples on how to specify the renewal period.

If the sum of the expire time and the renewal time is more than 10 years, we will reject your request.

This request is not working for domains, which are located on the old system. For these domains you have to check the documentation of the old system.

If you provide the expire year, this request will be rejected, if the current expire year is greater than the desired. This feature prevents an error in case 1 renew-request is sent twice by mistake.

Request fields

mailto:subject:renew-<ID>-domain [your reference ID]



# Domains

Definition of this request

You have to provide the domain name and the renewal period or the desired expiry year using the format "YYYY" on one line. You have to separate each field with a " " (ASCII 32). The maximum for the renewal period is 9 years.

domain	renewal period	expiry year
example.com	1	2025

COM renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew com-domain {your reference id}  
domain@minu-100.com.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew com-domain {your reference id}  
domain@minu-100.com.4  
domain@minu-110.com.4  
domain@minu-120.com.4  
domain@minu-130.com.4  
domain@minu-140.com.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew com-domain {your reference id}  
domain@minu-100.com.1  
domain@minu-110.com.2  
domain@minu-120.com.3  
domain@minu-130.com.4  
domain@minu-140.com.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew com-domain {your reference id}  
domain@minu-100.com.2005

NET Renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew net-domain {your reference id}  
domain@minu-100.net.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew net-domain {your reference id}  
domain@minu-100.net.4  
domain@minu-110.net.4  
domain@minu-120.net.4  
domain@minu-130.net.4  
domain@minu-140.net.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew net-domain {your reference id}  
domain@minu-100.net.1  
domain@minu-110.net.2  
domain@minu-120.net.3  
domain@minu-130.net.4  
domain@minu-140.net.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew net-domain {your reference id}  
domain@minu-100.net.2005

ORG Renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew org-domain {your reference id}  
domain@minu-100.org.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew org-domain {your reference id}  
domain@minu-100.org.4  
domain@minu-110.org.4  
domain@minu-120.org.4  
domain@minu-130.org.4  
domain@minu-140.org.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew org-domain {your reference id}  
domain@minu-100.org.1  
domain@minu-110.org.2  
domain@minu-120.org.3  
domain@minu-130.org.4  
domain@minu-140.org.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew org-domain {your reference id}  
domain@minu-100.org.2005

INFO Renewal

**Example 1:** renew 1 domain for 1 year using the field period  
subject: renew info-domain {your reference id}  
domain@minu-100.info.1

**Example 2:** renew 5 domains for 4 years using the field period  
subject: renew info-domain {your reference id}  
domain@minu-100.info.4  
domain@minu-110.info.4  
domain@minu-120.info.4  
domain@minu-130.info.4  
domain@minu-140.info.4

**Example 3:** renew 5 domains for different years using the field period  
subject: renew info-domain {your reference id}  
domain@minu-100.info.1  
domain@minu-110.info.2  
domain@minu-120.info.3  
domain@minu-130.info.4  
domain@minu-140.info.5

**Example 4:** renew 1 domain using the field expiryyear  
subject: renew info-domain {your reference id}  
domain@minu-100.info.2005

# Domains

## BIZ Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew biz-domain [your reference id]

domainid: min-us-biz-1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew biz-domain [your reference id]

domainid: min-us-biz-4

domainid: min-us-biz-4

domainid: min-us-biz-4

domainid: min-us-biz-4

domainid: min-us-biz-4

**Example 3:** renew 5 domains for different years using the field period

subject: renew biz-domain [your reference id]

domainid: min-us-biz-1

domainid: min-us-biz-2

domainid: min-us-biz-3

domainid: min-us-biz-4

domainid: min-us-biz-5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew biz-domain [your reference id]

domainid: min-us-biz-2005

## NAME Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew name-domain [your reference id]

domainid: min-us-name-1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew name-domain [your reference id]

domainid: min-us-name-4

domainid: min-us-name-4

domainid: min-us-name-4

domainid: min-us-name-4

domainid: min-us-name-4

**Example 3:** renew 5 domains for different years using the field period

subject: renew name-domain [your reference id]

domainid: min-us-name-1

domainid: min-us-name-2

domainid: min-us-name-3

domainid: min-us-name-4

domainid: min-us-name-5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew name-domain [your reference id]

domainid: min-us-name-2005

## US Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew us-domain [your reference id]

domainid: min-us-us-1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew us-domain [your reference id]

domainid: min-us-us-4

domainid: min-us-us-4

domainid: min-us-us-4

domainid: min-us-us-4

domainid: min-us-us-4

**Example 3:** renew 5 domains for different years using the field period

subject: renew us-domain [your reference id]

domainid: min-us-us-1

domainid: min-us-us-2

domainid: min-us-us-3

domainid: min-us-us-4

domainid: min-us-us-5

**Example 4:** renew 1 domain using the field expiry year

subject: renew us-domain [your reference id]

domainid: min-us-us-2005

## DE Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew de-domain [your reference id]

domainid: min-us-de-1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew de-domain [your reference id]

domainid: min-us-de-4

domainid: min-us-de-4

domainid: min-us-de-4

domainid: min-us-de-4

domainid: min-us-de-4

**Example 3:** renew 5 domains for different years using the field period

subject: renew de-domain [your reference id]

domainid: min-us-de-1

domainid: min-us-de-2

domainid: min-us-de-3

domainid: min-us-de-4

domainid: min-us-de-5

**Example 4:** renew 1 domain using the field expirationyear

subject: renew de-domain [your reference id]

domainid: min-us-de-2005

## CA Renewal

**Example 1:** renew 1 domain for 1 year using the field period

subject: renew ca-domain [your reference id]

domainid: min-us-ca-1

**Example 2:** renew 5 domains for 4 years using the field period

subject: renew ca-domain [your reference id]

domainid: min-us-ca-4

domainid: min-us-ca-4

domainid: min-us-ca-4

domainid: min-us-ca-4

domainid: min-us-ca-4

**Example 3:** renew 5 domains for different years using the field period

subject: renew ca-domain [your reference id]

domainid: min-us-ca-1

domainid: min-us-ca-2

domainid: min-us-ca-3

domainid: min-us-ca-4

domainid: min-us-ca-5

**Example 4:** renew 1 domain using the field expiry year

subject: renew ca-domain [your reference id]

domainid: min-us-ca-2005

Keywords: renew, renewal

# Domains

Last update: 2011-08-11 14:18

# Domains

## Transfer a domain

Introduction

Transfer .com domain

Valid values for .com:

- .com
- .net
- .org
- .biz
- .info
- .us
- .mobi
- .name
- .tv
- .co
- .cc

With this request you can transfer a domain from 1 registrar to Joker.com.  
You have to provide the following information within the request:

- the domain name,
- the auth-Id,
- the billing-contact-handle.

You can transfer 1 .com domain with one request.

If you transfer a domain to Joker.com the domain will be renewed for one year.

As you can see, we don't need information about the owner-contact. We will detect this information from the which of the current registrar and we will create the contact-handle for the owner-contact automatically.

You need to provide us with a so-called auth-Id. You have to ask the current registrar for this auth-Id. If you provide an invalid auth-Id, the transfer will be declined by the current registrar.

As you can see, we need the billing-contact-handle. We recommend using a billing-handle with the email-address of your "joker-email". If you use a contact-handle with a different email than your joker-email, you can't administer the transferred domain using the webinterface and the person with access to the email, which is shown in the provided billing-handle will have access using the web-interface.

If you don't have a com-contact-handle with your "joker-email", you have to create a com-handle using the "create-com-contact" request.



# Domains

```
domain@mouse 100.org  
auth-id=02023A48
```

```
bill@comcast-handls.COOC-1234
```

```
TRANSFER INFO DOMAIN  
Example 1: transfer info-domain  
subject: transfer info-domain [your reference id]  
domain@mouse 100.de  
auth-id=02023A48  
bill@comcast-handls.CITRUS-LRMS
```

```
TRANSFER BIZ DOMAIN  
Example 1: transfer biz-domain  
subject: transfer biz-domain [your reference id]  
domain@mouse 100.biz  
auth-id=02023A48  
bill@comcast-handls.CNEM-123
```

```
TRANSFER NAME DOMAIN  
Example 1: transfer name-domain  
subject: transfer name-domain [your reference id]  
domain@mouse 100.name  
auth-id=02023A48
```

```
bill@comcast-handls.CNAM-1234
```

```
TRANSFER US DOMAIN  
Example 1: transfer us-domain  
subject: transfer us-domain [your reference id]  
domain@mouse 100.us  
auth-id=02023A48
```

```
bill@comcast-handls.COUS-1234
```

```
TRANSFER DE DOMAIN  
Example 1: transfer de-domain  
subject: transfer de-domain [your reference id]  
domain@mouse 100.de  
auth-id=02023A48  
bill@comcast-handls.COOC-1234
```

```
TRANSFER CN DOMAIN  
Example 1: transfer cn-domain  
subject: transfer cn-domain [your reference id]  
domain@mouse 100.cn  
auth-id=02023A48  
bill@comcast-handls.COON-1234
```

Keywords: transfer, auth-id

Last update: 2011-08-11 14:14

# Domains

## Delete a domain

### Introduction

With this request you can delete a domain at joker.com.

You have to provide the following information within the request:

- domain name(s).
- the special flag force.

### ATTENTION

If you delete a domain within the first 72 hours after the registration, the registration fee will be refunded to your account.

If Joker.com receives the delete request more than 72 hours after the registration, you have to provide the flag "force": "1", in order to accept that the registration fee will not be refunded to your account. If you do not send the "force": "1" in such a case, the request will be rejected.

### Request fields

mailsubject: delete domain [your reference id]

Definition of this request

Please, do not forget to provide the domain name and the force-flag set to 1 if the domain is older 72h.

id	mailsubject	mailto
1	delete domain [your reference id]	webmaster@joker.com
2	delete domain [your reference id]	webmaster@joker.com
3	delete domain [your reference id]	webmaster@joker.com

# Domains

## DELETE COM DOMAIN

**Example 1:** delete a domain during the first 72 hours after registration  
subject: delete domain [your reference id]

tld:com  
sld:frezel

**Example 2:** delete a domain after the first 72 hours after registration  
subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:1

**Example 3:** delete a domain only for the case that a refund is possible!  
subject: delete domain [your reference id]

tld:com  
sld:frezel  
force:0

Keywords: delete-domain

Last update: 2011-08-11 15:45



# Domains

## List domains

### Introduction

list domains

With this request you can get a list (lexicographically sorted) of all the domains you have currently registered at joker.com. You have to provide the target registry within the request:

cto = cto.net

com = .net

net = .net

org = .org

info = .info

biz = .biz

mod = .mod

name = .mod

co = .co

co = .co

co = .co

co = .co

### LIMITATIONS

- Only 20,000 domains are listed. If you have more than 20,000 domains under 1 registry at joker.com, you have to track the domain names yourself.
- In case you have more than 20,000 domains at joker.com under 1 registry, this request will not work for you. The listing would be incomplete and it will be missing random domains.
- This request works only with the new joker.com system.

### Request fields

url=subject list domains [your reference id]

Definition of the request:

Field Name	Field Values	Example
url	subject list domains [your reference id]	url

### LIST DOMAINS

**Example 1:** list domains for .com-domains  
subject list domains [your reference id]  
target=com

**Example 2:** list domains for .net-domains  
subject list domains [your reference id]  
target=net

**Example 3:** list domains for .org-domains  
subject list domains [your reference id]  
target=org

**Example 4:** list domains for .info-domains  
subject list domains [your reference id]  
target=info

**Example 5:** list domains for .biz-domains  
subject list domains [your reference id]  
target=biz

# Domains

Example 6: list domains for .de-domains  
subject: list domains [your reference ID]  
target: de

Example 7: list domains for .cn-domains  
subject: list domains [your reference ID]  
target: cn

Keywords: list-domains

Last update: 2011-08-11 15:44

# Domains

## Lock a domain

Introduction

Lock domain

With this request you can lock a domain in order to prevent fraudulent transfer attempts. If a domain is locked, each transfer request from a foreign registrar will be declined.

You have to provide the following information within the request:

● domain name

You can lock 1 domain with one request.

Request fields

mailto:subject=lock domain [your reference id]

Definition of this request

Request field	Request value	Request type
subject	lock domain	text

Example 1: lock a domain

subject: lock domain [your reference id]

ipdn.milvus-100.com

Keywords: lock-domain, protection

Last update: 2011-08-11 15:46

# Domains

## Unlock a domain

Introduction

unlock domain

With this request you can unlock a domain. If you want to transfer a domain to a foreign registrar, the domain has to be unlocked.

You have to provide the following information within the request:

● domain name

You can unlock 1 domain with one request.

Request fields

mailsubject: unlock domain [your reference id]

Definitions of the request

Field	Definition	Example
mailsubject	unlock domain [your reference id]	unlock domain 123456789

Example 1: unlock a domain  
subject: unlock domain [your reference id]  
top: joker.com

Keywords: unlock-domain, protection

Last update: 2011-08-11 15:46

# Domains

## Get Auth-id

### Introduction

With this request you can retrieve the auth-id for a particular domain. That request is needed only for the TLDs: org/info.biz.

You have to provide the following information within the request:

- domain name

You can retrieve the auth-id for 1 domain with one request.

### Request fields

mailto:subject: get-auth-id [your-reference-id]

### Definition of the request

Field Name	Field Value	Field Name	Field Value	Field Name	Field Value	Field Name	Field Value
subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]	subject	get-auth-id [your-reference-id]

Example 1: retrieve the auth-id for a .org-domain  
subject: get-auth-id [your-reference-id]  
to: info@100.org

Example 2: retrieve the auth-id for a .biz-domain  
subject: get-auth-id [your-reference-id]  
to: info@100.biz

Example 3: retrieve the auth-id for a .info-domain  
subject: get-auth-id [your-reference-id]  
to: info@100.info

Keywords: transfer, auth-id

Last update: 2011-08-11 15:46

# Domains

## Grant Roles/Domain Permissions, Internal Transfer

Introduction

With this request you can assign [roles/permissions of domains](#) to other Joker.com users. The special role "creator" is an equivalent to an internal transfer of that domain to another Joker.com user. In this case, the domain is assigned to the receiving account, including all rights and permissions on this domain.

There are two variants to use this functionality. If the user id (Joker.com user account id) is given, and the account id matches the associated email address, the role is applied immediately - there will be no request for confirmation on the receiver's side. In case the user id is not given, but only the email address, the transaction has to be acknowledged by the receiver. For this, he will get an email, containing a link and a key. Either the link has to be clicked, or the key has to be applied using Joker.com (or Transfer). This can also be used for users which do not yet have a

Joker.com account

You have to provide the following parameters:

- domain name (the domain you want to grant somebody else permissions on)
- destination client email (the email address of the user you want to receive permissions)

The following parameters are optional:

- destination client id (ID of Joker.com account - always shown in the upper right on Joker.com, also conforms to "header id" - must match the destination client email)
- desired role (type of permission you want to assign to "client email" - help: "client id" - one of "admin@joker.com", "creator" means "all permissions" and is equivalent to an internal transfer or "assignment" - also see [links](#))

Request fields

request[id] joker-internal-transfer [your reference id]

Definition of this request

Valid values for id: @Joker.com ID

request field	value	required
id	[+40-9][0-9]{1,25}	yes
destination-client-email	<a href="#">@email</a>	yes
destination-client-id	[0-9]+	no
desired-role	admin@joker.com/creator (if omitted, default is "creator")	no

Example 1: assign "admin" role to user 123456 (demo)

# Domains

subject: jkdn-internal-transfer (pour référence id)

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

destination-client-id:123456

desired-role:billing

**Example 2:** assign 'creator'-role to user 'example-user@gmail.com' (internal transfer with invitation)

subject: jkdn-internal-transfer (pour référence id)

body:

fqdn:exampledomain.com

[destination-client-email:example-user@gmail.com](#)

desired-role:creator

Keywords: grants, roles, contacts, permissions, invitations

Last update: 2011-08-17 09:35

# Domains