

Account and Handling

login

Login with Username & Password

Requires (mandatory):

| | |
|----------|------------------------------------|
| username | Joker.com username (email address) |
| password | Joker.com password |

Returns:

| | |
|--------------|--|
| Auth-SID | Authenticated Session ID, must be provided with any other request (parameter <i>auth-sid</i>) |
| List of TLDs | List of domain TLDs which are available to the reseller. |

To be able to use the entire API, you must have a reseller account with Joker.com (and use this account to log in).

Example:

```
https://dmapi.joker.com/request/login?username=johndoe&password=myspass
```

Login with API Keys

Instead of using your user- and password credentials, you may also use so called '**API keys**' for login. This way, you can create several DMAPI access facilities, which has several advantages:

- you do not need to expose username and password in your scripts
- API keys **can be restricted** to be "read only" (no modifications possible), or to allow 'modifications only' (can not produce costs)
- you may hand API keys to your staff to enable them to do specific things with Joker.com

Create your API keys in ['My Profile'](#) in section '**Manage Joker.com API access keys**'

Account and Handling

Example usage:

```
https://dmapi.joker.com/request/login?api-key=Key_created_in_your_Profile_at_Joker.com
```

The result is the same as for "login"-request, you have to use the provided auth-sid for the subsequent actions.

Unique solution ID: #1015

Author: Joker.com

Last update: 2017-07-28 17:20