

Account and Handling result-list

Accepts:

pending

get results of requests still in progress

showall
period
date

get all results incl. deletes using result-delete
get results for specified period of days (default 7)
get results received on (or before) specified date
date is specified, parameter "period" will be ignored
date (instead of today) and defaults to 1

offset
limit
status
count-only

start displaying results from specified position
only get number of results specified by limit
get results having specified status (ack/nack)
when set to 1, only count number of records
single line in format "Records: N"

All following filters may use patterns ("*" and "?")

rtype

get results for requests of specified type (domain, register/etc)

objid

get results for specified object ids (domain, contacts, hosts)

procid

get results for specified proc-id

svtrid

get results for specified SvTrId

cltrid

get results for specified ClTrId

Returns:

List of answers from joker.com (one per line):

```
TimeStamp SvTrId Proc-ID request-type status ClTrId
```

Where:

TimeStamp: The time when request was made, YYYYMMDDHHMMSS

SvTrID: Tracking-Id associated with this request.

Proc-ID: Proc-Id associated with this request.

request-type: The type of the request.

request-object: The object name (host, domain or contact handle)

Account and Handling

status: ack, nack or ?, where ack means that request was completed successfully.

ClTrId: User specified transaction ID, or "-" if nothing was provided by the user

Example:

<https://dmapi.joker.com/request/result-list?auth-sid=20ddb8c3b2ea758dcf9fa4c7f46c0784>

Unique solution ID: #1017

Author: Joker.com

Last update: 2019-12-18 15:56